STATE OF MAINE DEPARTMENT OF ENVIRONMENTAL PROTECTION



PAUL R. LEPAGE GOVERNOR



PATRICIA W. AHO COMMISSIONER

October 20, 2014

Mr. Stephen Freeman Superintendent Presque Isle Utilities District P.O. Box 470 Presque Isle, ME 04769 sfreeman@maine.rr.com

Transmitted via electronic mail Delivery confirmation requested

RE:

Maine Pollutant Discharge Elimination System (MEPDES) Permit #ME0102679

Maine Waste Discharge License (WDL) Application #W002618-5S-E-R

Final Permit

Dear Mr. Freeman:

Enclosed please find a copy of your final MEPDES permit and Maine WDL renewal which was approved by the Department of Environmental Protection. Please read this permit/license renewal and its attached conditions carefully. You must follow the conditions in the order to satisfy the requirements of law. Any discharge not receiving adequate treatment is in violation of State Law and is subject to enforcement action.

Any interested person aggrieved by a Department determination made pursuant to applicable regulations, may appeal the decision following the procedures described in the attached DEP FACT SHEET entitled "Appealing a Commissioner's Licensing Decision."

If you have any questions regarding the matter, please feel free to call me at 215-1579 or send me an e-mail at yvette.meunier@maine.gov.

Sincerely, frette Meunier

Yvette Meunier

Division of Water Quality Management

Bureau of Land and Water Quality

Enc.

cc:

Bill Sheehan, DEP/NMRO

Sandy Mojica, USEPA Marelyn Vega, USEPA OlgaVergara, USEPA



STATE OF MAINE DEPARTMENT OF ENVIRONMENTAL PROTECTION 17 STATE HOUSE STATION AUGUSTA, MAINE 04333-0017

DEPARTMENT ORDER

IN THE MATTER OF

PRESQUE ISLE UTILITIES DISTRICT)	MAINE POLLUTANT DISCHARGE
PRESQUE ISLE, AROOSTOOK COUNTY, I	MAINE)	ELIMINATION SYSTEM PERMIT
DRINKING WATER TREATMENT FACILI	TY)	AND
#ME0102679)	WASTE DISCHARGE LICENSE
#W002618-5S-E-R APPROVAL)	RENEWAL

In compliance with the Federal Water Pollution Control Act, Title 33 USC, §1251, Conditions of licenses, 38 M.R.S.A. § 414-A, and applicable regulations, the Department of Environmental Protection (Department) has considered the application of the PRESQUE ISLE UTILITIES DISTRICT (PIUD), with its supportive data, agency review comments, and other related materials on file and FINDS THE FOLLOWING FACTS:

APPLICATION SUMMARY

The PIUD submitted a timely and complete application to the Department for renewal of Waste Discharge License (WDL) #W002618-5S-D-R / Maine Pollutant Discharge Elimination System (MEPDES) permit #ME0102679, which was issued on October 16, 2009 for a five-year term. The 10/16/09 MEPDES permit authorized monthly average discharge of 0.180 million gallons per day (MGD) of filter cleaning (backwash) wastewater from a municipal drinking water treatment plant to Presque Isle Stream, Class B, in Presque Isle, Maine.

PERMIT SUMMARY

This permitting action is carrying forward all the terms and conditions of the previous permitting action except it is:

1. Eliminating the concentration limit for aluminum.

CONCLUSIONS

Based on the findings summarized in the attached Fact Sheet dated October 20, 2014, and subject to the Conditions listed below, the Department makes the following CONCLUSIONS:

- 1. The discharge, either by itself or in combination with other discharges, will not lower the quality of any classified body of water below such classification.
- 2. The discharge, either by itself or in combination with other discharges, will not lower the quality of any unclassified body of water below the classification which the Department expects to adopt in accordance with state law.
- 3. The provisions of the State's antidegradation policy, *Classification of Maine waters*, 38 M.R.S.A. § 464(4)(F), will be met, in that:
 - (a) Existing in-stream water uses and the level of water quality necessary to protect and maintain those existing uses will be maintained and protected;
 - (b) Where high quality waters of the State constitute an outstanding natural resource, that water quality will be maintained and protected;
 - (c) The standards of classification of the receiving water body are met or, where the standards of classification of the receiving water body are not met, the discharge will not cause or contribute to the failure of the water body to meet the standards of classification;
 - (d) Where the actual quality of any classified receiving water body exceeds the minimum standards of the next highest classification that higher water quality will be maintained and protected; and
 - (e) Where a discharge will result in lowering the existing water quality of any water body, the Department has made the finding, following opportunity for public participation, that this action is necessary to achieve important economic or social benefits to the State.
- 4. The discharges will be subject to effluent limitations that require application of best practicable treatment as defined in 38 M.R.S.A. § 414-A(1)(D).

ACTION

THEREFORE, the Department APPROVES the above noted application of the PRESQUE ISLE UTILITIES DISTRICT to discharge a monthly average of 0.180 million gallons per day (MGD) of filter cleaning (backwash) wastewater from a municipal drinking water treatment plant to Presque Isle Stream, Class B, in Presque Isle, Maine, SUBJECT TO THE ATTACHED CONDITIONS, and all applicable standards and regulations including:

- 1. Maine Pollutant Discharge Elimination System Permit Standard Conditions Applicable To All Permits, revised July 1, 2002, copy attached.
- 2. The attached Special Conditions, including any effluent limitations and monitoring requirements.
- 3. This permit and the authorization to discharge become effective upon the date of signature below and expire at midnight five (5) years from the effective date. If a renewal application is timely submitted and accepted as complete for processing prior to the expiration of this permit, the authorization to discharge and the terms and conditions of this permit and all modifications and minor revisions thereto remain in effect until a final Department decision on the renewal application becomes effective. [Maine Administrative Procedure Act, 5 M.R.S.A. § 10002 and Rules Concerning the Processing of Applications and Other Administrative Matters, 06-096 CMR 2(21)(A) (amended August 25, 2013)]

PLEASE NOTE ATTACHED SHEET FOR GUIDANCE ON APPEAL PROCEDURES

DONE AND DATED AT AUGUSTA, MAINE, THIS 17	th DAY OF October 2014
DEPARTMENT OF ENVIRONMENTAL PROTECTION	
	Filed
BY: Michael Luliano PATRICIA W. AHÒ, Commissioner	OCT 2 0 2014
	State of Maine Board of Environmental Protection
Date filed with Board of Environmental Protection	

Date of initial receipt of application: <u>August 4, 2014</u>
Date of application acceptance: <u>August 4, 2014</u>

This Order prepared by Yvette Meunier, BUREAU OF LAND & WATER QUALITY

Page 4 of 9

SPECIAL CONDITIONS

A. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS

1. The permittee is authorized to discharge drinking water filter cleaning (backwash) wastewater from Outfall #001 (Southern Lagoon) to the Presque Isle Stream. Such discharges are limited and must be monitored by the permittee as specified below (4, 2):

N T T NS						Minimum	mm
Monthly Average Maximum Average Monthly Average Monthly Average Daily Average Monthly Average Maximum Aver	Effluent Characteristic		Discha	rge Limitations		Monitoring Requirements	equirements
Average Maximum Average Maximum 1 0.090 MGD — — — 1 (0.93) — — — — 1 (2.2) 15s/day 45 1bs/day 30 mg/L 60 mg/L [19] 1 Residual Chlorine — — [2.5] — [2.5] 1 Aluminum 1.8 1bs/day — — — [1.9] 1 — — — — [1.9] 1 — — — — — 1.8 1bs/day — — — — 1 — — — — 1 — — — — 1 — — — — 1 [1.9] — — — — 1 — — — — — 1 — — — — —		Monthly	Daily	Monthly	Daily	Measurement	Sample
0.090 MGD		Average	Maximum	Average	Maximum	Frequency	Type
O.090 MGD	Flow	0000				When	Coloniate
22 lbs/day 45 lbs/day 30 mg/L 60 mg/L 199] 199	[50050]	0.090 MGD	!	*****		Discharging	Calculate [CA]
1 22 1bs/day 45 1bs/day 30 mg/L 60 mg/L 119j 118		F-07				[WH/DS]	f7
Page	TSS	22 lbs/day	45 lbs/day	30 mg/L	60 mg/L	1/Month	Composite ⁽³⁾
tleable Solids — 0.3 ml/L 125j al Residual Chlorine — 0.15 mg/L 1 sol — — (19j) al Aluminum 1.8 lbs/day — — — osj [26j] — 6.0 – 8.5 SU — ooj — [12j]	[00530]	[26]	[56]	[19]	[61]	[01/30]	[CP]
45J — [25] al Residual Chlorine — 0.15 mg/L 1 60J — [19J] — al Aluminum 1.8 lbs/day — — — 05J — — 6.0 – 8.5 SU — 00J — [12] —	Settleable Solids				0.3 ml/L	1/Month	Grab
al Residual Chlorine 0.15 mg/L 1 60J I19J 1 al Aluminum 1.8 lbs/day 1 05J 6.0 - 8.5 SU 1/2J	[00545]	!	440 000 044	1	[25]	[01/30]	[GR]
al Aluminum 1.8 lbs/day 057 (26f) 1.8 lbs/day (26f) (6.0 - 8.5 SU 1/2]	Total Residual Chlorine				0.15 mg/L	1/Month	Grab
al Aluminum 1.8 lbs/day 6.0 - 8.5 SU	[50060]				[19]	[01/30]	[GR]
063	Total Aluminum	1.8 Ibs/day				1/Month	Grab
00] 6.0 -8.5 SU	[01105]	[26]		•	dam para-para	[01/30]	[GR]
[12]	Hd				0.0 - 8.5 SU	1/Month	Grab
	[00400]		1 1 1	!	[12]	[01/30]	[GR]

The italicized numeric values bracketed in the table and in subsequent text are code numbers that Department personnel utilize to code the monthly Discharge Monitoring

FOOTNOTES: See Page 6 of this permit for applicable footnotes.

Page 5 of 9

PERMIT

SPECIAL CONDITIONS

A. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS

1. The permittee is authorized to discharge drinking water filter cleaning (backwash) wastewater from Outfall #002 (Northern Lagoon) to the Presque Isle Stream. Such discharges are limited and must be monitored by the permittee as specified below (1,2):

					Minimum	mn
Effluent Characteristic		Discha	Discharge Limitations		Monitoring Requirements	equirements
	Monthly Average	Daily Maximum	Monthly Average	Daily Maximum	Measurement Frequency	Sample Type
Flow [50050]	0.090 MGD [03]	1 1	4 7 7	- 7 - 7	When Discharging [WH/DS]	Calculate [CA]
TSS 100530J	22 lbs/day [26]	45 lbs/day <i>[26]</i>	$30~\mathrm{mg/L}$ $I19J$	1/gm 09 1/61]	1/Month [01/30]	Composite ⁽³⁾ [CP]
Settleable Solids [00545]	-		-	0.3 ml/L [25]	1/Month [01/30]	Grab [GR]
Total Residual Chlorine [50060]			-	$0.15~\mathrm{mg/L}_{I19J}$	1/Month [01/30]	Grab [GR]
Total Aluminum [01105]	1.8 lbs/day [26]	to paras		***************************************	1/Month [01/30]	Grab [GR]
pH [00400]	1	1	a a a	6.0 – 8.5 SU [12]	1/Month [01/30]	Grab [GR]

The italicized numeric values bracketed in the table and in subsequent text are code numbers that Department personnel utilize to code the monthly Discharge Monitoring Reports.

FOOTNOTES: See Page 6 of this permit for applicable footnotes.

SPECIAL CONDITIONS

A. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS (cont'd)

FOOTNOTES

1. Sampling – The permittee must conduct sampling and analysis in accordance with; a) methods approved by 40 Code of Federal Regulations (CFR) Part 136, b) alternative methods approved by the Department in accordance with the procedures in 40 CFR Part 136, or c) as otherwise specified by the Department. Samples that are sent out for analysis must be analyzed by a laboratory certified by the State of Maine's Department of Health and Human Services. Samples that are sent to a POTW licensed pursuant to Waste discharge licenses, 38 M.R.S.A. § 413 are subject to the provisions and restrictions of Maine Comprehensive and Limited Environmental Laboratory Certification Rules, 10-144 CMR 263 (last amended February 13, 2000). If the permittee monitors any pollutant more frequently than required by the permit using test procedures approved under 40 CFR Part 136 or as specified in this permit, the results of this monitoring must be included in the calculation and reporting of the data submitted in the Discharge Monitoring Report.

All analytical test results from monitoring of parameters required by this license shall be reported to the Department including results which are quantified below the respective reporting limits (RLs) specified by the Department or as specified by other approved test methods. A non-detect analytical test result shall be reported as <Y where Y is the minimum level for reporting quantitative data specified by the laboratory in their report for each respective parameter. Reporting a value of <Y that is greater than an established RL is not acceptable and will be rejected by the Department. Lab data that have an estimated value ("J" flagged) below an established RL shall be reported as "< RL". Reporting analytical data and its use in calculations must follow established Department guidelines specified in this permit or in available Department guidance documents.

- 2. **Authorized Discharges** The effluent limitations and monitoring requirements apply to the total combined discharge from both Outfall #001 and Outfall #002 whether discharging simultaneously or individually.
- 3. **Composite samples.** Composite means a combined sample consisting of one grab sample collected during each minute of the initial 15-minute backwash phase of the regeneration cycle.

B. NARRATIVE EFFLUENT LIMITATIONS

- 1. The permittee must not discharge effluent that contains a visible oil sheen, foam or floating solids at any time which would impair the usages designated for the classification of the receiving waters.
- 2. The permittee must not discharge effluent that contains materials in concentrations or combinations which are hazardous or toxic to aquatic life, or which would impair the usages designated for the classification of the receiving waters.
- 3. The permittee must not discharge effluent that causes visible discoloration or turbidity in the receiving waters or that impairs the usages designated for the classification of the receiving waters.

SPECIAL CONDITIONS

B. NARRATIVE EFFLUENT LIMITATIONS (cont'd)

4. The permittee must not discharge effluent that lowers the quality of any classified body of water below such classification, or lowers the existing quality of any body of water if the existing quality is higher than the classification.

C. AUTHORIZED DISCHARGES

The permittee is authorized to discharge only in accordance with: 1) the permittee's General Application for Waste Discharge Permit, accepted for processing on August 4, 2014; 2) the terms and conditions of this permit; and 3) only from Outfalls #001 and #002. Discharges of wastewater from any other point source(s) are not authorized under this permit, and must be reported in accordance with Standard Condition B(5), *Bypasses*, of this permit.

D. NOTIFICATION REQUIREMENT

In accordance with Standard Condition D, the permittee must notify the Department of the following:

- 1. Any introduction of pollutants into the wastewater collection and treatment system from an indirect discharger in a primary industrial category discharging process wastewater; and
- 2. Any substantial change in the volume or character of pollutants being introduced into the wastewater collection and treatment system by a source introducing pollutants to the system at the time of permit issuance. For the purposes of this section, notice regarding substantial change must include information on:
 - (a) the quality and quantity of wastewater introduced to the wastewater collection and treatment system; and
 - (b) any anticipated impact caused by the change in the quantity or quality of the wastewater to be discharged from the treatment system.

E. MONITORING AND REPORTING

Monitoring results obtained during the previous month must be summarized for each month and reported on separate Discharge Monitoring Report (DMR) forms provided by the Department and postmarked on or before the thirteenth (13th) day of the month or hand-delivered to the Department's Regional Office such that the DMRs are received by the Department on or before the fifteenth (15th) day of the month following the completed reporting period. A signed copy of the DMR and all other reports required herein must be submitted to the Department assigned inspector

#ME0102679 #W002618-5S-D-R

E. MONITORING AND REPORTING (cont'd)

(unless otherwise specified by the Department) at the following address:

Department of Environmental Protection Northern Maine Regional Office Bureau of Land and Water Quality Division of Water Quality Management 1235 Skyway Park Presque Isle, Maine 04769

Alternatively, if the permittee submits an electronic DMR (eDMR), the completed eDMR must be electronically submitted to the Department by a facility authorized DMR Signatory not later than close of business on the 15th day of the month following the completed reporting period. Hard copy documentation submitted in support of the eDMR must be postmarked on or before the thirteenth (13th) day of the month or hand-delivered to the Department's Regional Office such that it is received by the Department on or before the fifteenth (15th) day of the month following the completed reporting period. Electronic documentation in support of the eDMR must be submitted not later than close of business on the 15th day of the month following the completed reporting period.

F. OPERATIONS AND MAINTENANCE (O&M) PLAN

The permittee must maintain a current written comprehensive Operation & Maintenance (O&M) Plan for the facility. The plan must provide a systematic approach by which the permittee must at all times, properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the permittee to achieve compliance with the conditions of this permit.

By December 31 of each year, or within 90 days of any process changes or minor equipment upgrades, the permittee must evaluate and modify the O&M Plan including site plan(s) and schematic(s) for the wastewater treatment facility to ensure that it is up-to-date. The O&M Plan must be kept on-site at all times and made available to Department and U.S. Environmental Protection Agency (USEPA) personnel upon request.

Within 90 days of completion of new and or substantial upgrades of the wastewater treatment facility, the permittee must submit the updated O&M Plan to their Department inspector for review and comment.

G. REOPENING OF PERMIT FOR MODIFICATION

In accordance with 38 M.R.S.A. § 414-A(5) and upon evaluation of the tests results or monitoring requirements specified in Special Conditions of this permitting action, new site specific information, or any other pertinent test results or information obtained during the term of this permit, the Department may, at any time and with notice to the permittee, modify this permit to: 1) include effluent limits necessary to control specific pollutants or whole effluent toxicity where there is a reasonable potential that the effluent may cause water quality criteria to be exceeded, (2) require additional monitoring if results on file are inconclusive; or (3) change monitoring requirements or limitations based on new information.

H. SEVERABILITY

In the event that any provision(s), or part thereof, of this permit is declared to be unlawful by a reviewing court, the remainder of the permit must remain in full force and effect, and must be construed and enforced in all aspects as if such unlawful provision, or part thereof, had been omitted, unless otherwise ordered by the court.

MAINE POLLUTANT DISCHARGE ELIMINATION SYSTEM PERMIT MAINE WASTE DISCHARGE LICENSE

FACT SHEET

DATE:

OCTOBER 20, 2014

PERMIT NUMBER:

#ME0102679

WASTE DISCHARGE LICENSE:

#W002631-5S-E-R

NAME AND ADDRESS OF APPLICANT:

PRESQUE ISLE UTILITIES DISTRICT

P.O. BOX 470

PRESQUE ISLE, MAINE 04769

COUNTY:

AROOSTOOK

NAME AND ADDRESS WHERE DISCHARGE(S) OCCUR(S):

PRESOUE ISLE UTILITIES DISTRICT

176 CHAPMAN STREET

PRESQUE ISLE, MAINE 04769

RECEIVING WATER CLASSIFICATION: PRESQUE ISLE STREAM/CLASS B

COGNIZANT OFFICIAL CONTACT INFORMATION:

MR. STEPHEN FREEMAN

(207) 762-5061

sfreedman@maine.rr.com

1. APPLICATION SUMMARY

<u>Application</u>: The Presque Isle Utilities District (PIUD) submitted a timely and complete application to the Department of Environmental Protection (Department) for renewal of Waste Discharge License (WDL) #W002618-5S-D-R / Maine Pollutant Discharge Elimination System (MEPDES) permit #ME0102679, which was issued on October 16, 2009 for a five-year term. The 10/16/09 MEPDES permit authorized monthly average discharge of 0.180 million gallons per day (MGD) of filter cleaning (backwash) wastewater from a municipal drinking water treatment plant to Presque Isle Stream, Class B, in Presque Isle, Maine.

2. PERMIT SUMMARY

- a. <u>Terms and Conditions</u>: This permitting action is carrying forward all the terms and conditions of the previous permitting action except it is:
 - 1. Eliminating the concentration limit for aluminum.
- b. History: The most current relevant regulatory actions include:

May 2, 1995 – The Department issued Waste Discharge License (WDL) #W002618-ZA-B-R to the PIUD for the daily maximum discharge of 0.18 MGD of filter backwash wastewater to Presque Isle Stream in Presque Isle. This licensing action superseded previous WDL #W002618-45-A-R issued on February 22, 1984 and WDL #2618 issued on February 14, 1979, and expired on May 2, 2000.

November 15, 1996 – The US Environmental Protection Agency (USEPA) issued National Pollution Discharge Elimination System (NPDES) General Permit #MEG640004 to the PIUD for the discharge of filter backwash wastewater to Presque Isle Stream, which expired on November 15, 2001. The outfall pipe identifier used in MEG640004 was Outfall #001A. General Permit #MEG640004 superseded previous NPDES permit #ME0001295 issued by the USEPA. The outfall identifier used in #ME0001295 was Outfall #001D.

November 15, 1996 – The Department inactivated the PIUD facility under #ME0001295 in the permit compliance system (PCS) database to reflect that the facility was now permitted under NPDES General Permit #MEG640004.

May 2, 2000 – The PCS database contained an error in that it listed the effluent limits end date associated with the PIUD's discharge as May 2, 2000 to coincide with the expiration date of WDL #W002618-ZA-B-R. Therefore, the PIUD did not continue to receive monthly discharge monitoring reports (DMRs) after the expiration date (May 2, 2000) of the 5/2/95 WDL.

March 31, 2001 – The Department inactivated the PIUD facility under #MEG640004 in the PCS database and the history of why this facility was inactivated prior to the renewal of the 5/2/95 WDL is not known.

July 30, 2001 –The PIUD submitted a General Application for the renewal of WDL #W002618-ZA-B-R. The application was accepted for processing on July 31, 2001, and was assigned WDL #W002618-5S-C-R. The PIUD is listed as an inactive facility in the PCS system under both ME0001295 and ME640004; therefore, the Department assigned a new MEPDES number of ME0102679 to the PIUD in order to ensure the proper management of effluent data reported by the facility.

November 23, 2004 – The Department issued combination MEPDES permit #ME0102679/ Maine WDL #W002618-5S-C-R, for a five-year term.

2. PERMIT SUMMARY (cont'd)

October 16, 2009 – The Department issued combination MEPDES permit #ME0102679/Maine WDL #W002618-5S-C-R, for a five-year term.

August 4, 2014 – The PIUD submitted a timely and complete General Application to the Department for renewal of the 10/16/09 MEPDES permit. The application was accepted for processing on August 4, 2014, and was assigned WDL # W002618-5S-E-R / MEPDES #ME0102679.

c. Source Description: In a letter accompanying the 8/4/14 application for permit renewal, the PIUD stated that they have developed a ground water source to completely replace the surface water source. As of February 2010, the water filtration plant has not been operated. The surface water system will be utilized as an emergency water supply. As result, the MEPDES permit remains necessary if activation of the emergency water supply is realized.

The PIUD operates a municipal drinking water treatment facility on Chapman Street in Presque Isle to provide potable water to approximately 2,300 residential and commercial customers in the City of Presque Isle. A map showing the PIUD facility and the location of the two associated outfall points is included as Fact Sheet **Attachment A**. The facility was constructed in 1960 and the PIUD currently produces approximately 1.0 million gallons of potable water per day.

The PIUD obtains raw water from an impoundment on the Presque Isle Stream created by the Presque Isle Stream Dam. Under normal operating conditions, raw water is pumped to the facility during normal business hours using three pumps. Aluminum sulfate is injected into the raw water line prior to entering the treatment facility to assist in flocculation. The flow is then conveyed to a 280,000-gallon sedimentation basin that is partitioned into two nearly equal chambers. The first chamber serves as a flocculation chamber and the second chamber serves as a settling chamber. It is noted that the flow is treated with sodium aluminate in addition to the aluminum sulfate during the cool weather seasons (typically, September through May) and with a non-ionic polymer during the warm weather seasons (typically April through December) to further assist in floc formation and settling. Following settling, the flow is pre-chlorinated to a residual concentration of between 0.5 and 1.0 parts per million (ppm) using liquid chlorine to reduce bacterial growth on the filter media and is then evenly distributed to four (4) down-flow, rapid sand filtration beds. Each filter bed measures approximately 15-feet by 15-feet deep (2,250 cubic feet).

Filtered water is pumped to a 260,000-gallon clearwell and is treated with sodium hypochlorite (residual concentration of approximately 2.0 ppm) for disinfection, hydroflorosilicic acid for consumer dental protection, and caustic soda for pH adjustment. Finished water is then pumped to the distribution system, which includes two (2) 1,000,000-gallon capacity floating storage tanks located on State Street in Presque Isle and two additional storage tanks.

2. PERMIT SUMMARY (cont'd)

d. Wastewater Treatment: On average, the PIUD performs a total of two filter backwash cycles per day using finished water from the facility clearwell to ensure efficient operation of the filter beds. Each filter cleaning cycle is triggered based on filter head loss, filter break-through as measured by turbidity meters, or a pre-determined setpoint based on operator observations of system performance. Backwash cycles alternate such that only one filter bed is backwashed at any given time. Each backwash cycle generates approximately 27,000 gallons of wastewater and the PIUD performs two backwash cycles per day, on average, resulting in approximately 54,000 gallons of wastewater. It is noted that the PIUD generates more than 54,000 gallons of wastewater per day during periodic lagoon maintenance activities in which the lagoons are partially de-watered and during periods of high river turbidity when the filters must be backwashed at a more frequent interval.

The filter backwash cycle is initiated manually with a 10-minute up-flow filter backwash cycle using finished water at a rate of 2,700 gallons per minute. Following the up-flow sequence, the operator places the filter bed back into production mode by closing the backwash drain valve and reopening the raw water influent valve. Backwash wastewater is conveyed to one of two (2) available 380,000-gallon earthen settling lagoons at the treatment facility. The unlined lagoons were constructed in 1975 to provide an approximately 1-2 day detention period and each cell has a separate outfall structure to convey treated wastewater to the receiving water.

As noted above, final effluent is conveyed for discharge to Presque Isle Stream via Outfall #001 (southern lagoon) and Outfall #002 (northern lagoon). Typically the discharge occurs on an alternating basis, however this permitting action (as with the previous permit) authorizes the discharge from both outfall points concurrently subject to the effluent limits and monitoring requirements established in Special Condition A of this permit. The permittee is required to perform effluent monitoring for both outfall points and shall report "NODI-9" on the monthly discharge monitoring reports (DMRs) if there is no discharge from one or the other outfall during the monthly reporting period. Effluent is conveyed from the outlet structure of each lagoon cell through an approximately 20-foot long rock-lined ditch to Presque Isle Stream. There is no pipe connecting the lagoons to the receiving waters. Thus, the discharge is considered a bank outfall that does not achieve complete and rapid mixing of the effluent with the receiving water. A schematic of the PIUD's wastewater treatment process is included as Fact Sheet Attachment B.

The PIUD reported that they remove sludge from the sedimentation basin and each lagoon cell on an annual basis and land apply the material on local farm fields in accordance with applicable Maine laws and Department rules.

3. CONDITIONS OF PERMIT

Conditions of licenses, 38 M.R.S.A. § 414-A, requires that the effluent limitations prescribed for discharges, including, but not limited to, effluent toxicity, require application of best practicable treatment (BPT), be consistent with the U.S. Clean Water Act, and ensure that the receiving waters attain the State water quality standards as described in Maine's Surface Water Classification System. In addition, 38 M.R.S.A. § 420 and 06-096 CMR 530 require the regulation of toxic substances not to exceed levels set forth in Surface Water Quality Criteria for Toxic Pollutants, 06-096 CMR 584 (last amended July 29, 2012), and that ensure safe levels for the discharge of toxic pollutants such that existing and designated uses of surface waters are maintained and protected.

4. RECEIVING WATER QUALITY STANDARDS

Classification of major river basins, 38 M.R.S.A. § 467(15)(C)(2)(a) classifies "All tributaries of the Aroostook River entering below the confluence of the Machias River that are not otherwise classified as Class B waters." Standards for classification of fresh surface waters, 38 M.R.S.A. § 465(3) describes the standards for Class B waters.

5. RECEIVING WATER QUALITY CONDITIONS

The State of Maine 2012 Integrated Water Quality Monitoring and Assessment Report, prepared by the Department pursuant to Sections 303(d) and 305(b) of the Federal Water Pollution Control Act, lists a 1.0-mile section (Segment ID 140R03) of Presque Isle Stream in Presque Isle as, "Category 4-A Rivers and Streams with Impaired Use other than Mercury, TMDL Completed." The impaired use in this context refers to the aquatic life standard caused by ammonia (un-ionized), biochemical oxygen demand and total phosphorous.

In addition, all freshwaters in Maine are listed as "Category 4-A: Waters Impaired by Atmospheric Deposition of Mercury." Impairment in this context refers to a statewide fish consumption advisory due to elevated levels of mercury in some fish tissues. The Report states, "All freshwaters are listed in Category 4-A (TMDL Completed) due to USEPA approval of a Regional Mercury TMDL. Maine has a fish consumption advisory for fish taken from all freshwaters due to mercury. Many waters, and many fish from any given water, do not exceed the action level for mercury. However, because it is impossible for someone consuming a fish to know whether the mercury level exceeds the action level, the Maine Department of Health and Human Services decided to establish a statewide advisory for all freshwater fish that recommends limits on consumption. Maine has already instituted statewide programs for removal and reduction of mercury sources." Pursuant to 38 M.R.S.A. § 420(1-B)(B), "a facility is not in violation of the ambient criteria for mercury if the facility is in compliance with an interim discharge limit established by the Department pursuant to section 413 subsection 11." The Department has established interim monthly average and daily maximum mercury concentration limits and reporting requirements for this facility pursuant to 06-096 CMR 519.

5. RECEIVING WATER QUALITY CONDITIONS (cont'd)

The Department has no information at this time that the discharge from the PIUD, as permitted, will cause or contribute to the failure of the receiving water to meet the designated uses of its ascribed classification.

6. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS

Applicability of Tiered Effluent Limitations and Monitoring Requirements: The effluent limits established in this permitting action represent the maximum authorized discharge limits for the combined discharge from Outfall #001 and Outfall #002 whether simultaneously or individually. It is noted that there was no discharge from the Northern Lagoon (Outfall #002) during the last five years; therefore no data has been summarized for Outfall #002 in the fact sheet.

a. <u>Flow:</u> The previous permitting action established, and this permitting action is carrying forward, a monthly average discharge flow limit of 0.090 MGD based on current wastewater generation rates and a monitoring frequency of "continuous when discharging."

The Department reviewed 3 Discharge Monitoring Reports (DMRs) that were submitted for the period November 2009 – May 2014. A review of data indicates the following:

Flow - Outfall #001 (Southern)

Value	Limit (MGD)	Range (MGD)	Mean (MGD)
Monthly Average	0.090	0.000 - 0.010	0.004

b. <u>Dilution Factors</u>: Dilution factors associated with the permitted discharge flow of 0.090 MGD were derived in accordance with 06-096 CMR 530(4)(A) and were calculated as follows:

Mod. Acute:
$$\frac{1}{4}$$
 Q10 = 1.0 cfs $\Rightarrow \frac{(1.0 \text{ cfs})(0.6464) + 0.090 \text{ MGD}}{0.090 \text{ MGD}} = 8.2:1$

Acute:
$$1Q10 = 4.3 \text{ cfs}$$
 $\Rightarrow (4.3 \text{ cfs})(0.6464) + 0.090 \text{ MGD} = 31.9:1$
 0.090 MGD

Chronic:
$$7Q10 = 4.9 \text{ cfs}$$
 $\Rightarrow (4.9 \text{ cfs})(0.6464) + 0.090 \text{ MGD} = 36.2:1$
0.090 MGD

Harmonic Mean:
$$7Q10 = 14.7 \text{ cfs}$$
 $\Rightarrow (14.7 \text{ cfs})(0.6464) + 0.090 \text{ MGD} = 107:1$
0.090 MGD

06-096 CMR 530(4)(B)(1) states,

Analyses using numerical acute criteria for aquatic life must be based on 1/4 of the 1Q10 stream design flow to prevent substantial acute toxicity within any mixing zone and to ensure a zone of passage of at least 3/4 of the cross-sectional area of any stream as required by Chapter 581. Where it can be demonstrated that a discharge achieves rapid and complete mixing with the receiving water by way of an efficient diffuser or other effective method, analyses may use a greater proportion of the stream design flow, up to and including all of it, as long as the required zone of passage is maintained.

Effluent is discharged to the Presque Isle Stream via a rock-lined conveyance, therefore, the discharge from the PIUD is considered bank discharge that does not result in complete and rapid mixing of the effluent with the receiving waters. Consequently, the Department is utilizing the default stream flow of ¼ of the 1Q10 in acute evaluations pursuant to Chapter 530.

c. <u>Total Suspended Solids (TSS)</u>: This permitting action is carrying forward the previously established monthly average and daily maximum concentration limits of 30 mg/L and 60 mg/L, respectively, based on Department best professional judgment of best practicable treatment for discharges from drinking water treatment facilities in Maine. The previous permit carried forward the monthly average mass limit for TSS and revised the daily maximum mass limit based on the following calculations.

Monthly Average Mass: (30 mg/L)(8.34 lbs./gallon)(0.090 MGD) = 22 lbs./dayDaily Maximum Mass: (60 mg/L)(8.34 lbs./gallon)(0.090 MGD) = 45 lbs./day

The Department reviewed 3 Discharge Monitoring Reports (DMRs) that were submitted for the period November 2009 – May 2014. A review of data indicates the following:

TSS mass - Outfall #001 (Southern)

Value	Limit (lbs./day)	Range (lbs./day)	Mean (lbs./day)
Monthly Average	22	0.00 - 0.30	0.13
Daily Maximum	45	0.10 - 0.30	0.17

TSS concentration - Outfall #001 (Southern)

100 concentration	Outlant Hook (Southers		
Value	Limit (mg/L)	Range (mg/L)	Mean (mg/L)
Monthly Average	30	1.00 -6.00	4.33
Daily Maximum	60	1.00 - 6.00	4.33

This permitting action is carrying forward a minimum monitoring frequency requirement of once per month for TSS based on Department best professional judgment.

d. Settleable Solids: The previous permitting action established, and this permitting action is carrying forward a daily maximum concentration limit of 0.3 ml/L for Outfall #001 and Outfall #002 as a BPT requirement along with a once per month (1/Month) monitoring requirement based on a Department BPJ determination of the minimum level of monitoring necessary to assess compliance with this parameter.

The Department reviewed 3 Discharge Monitoring Reports (DMRs) that were submitted for the period November 2009 – May 2014. A review of data indicates the following:

Settleable solids concentration - Outfall #001 (Southern)

Setticante annos conce	Hilation - Outlan		
Value	Limit (ml/L)	Range (ml/L)	Average (ml/L)
Daily Maximum	0.3	0.1 - 0.1	0.1

e. <u>Total Residual Chlorine (TRC)</u>: The PIUD utilizes chlorinated water for filter cleaning procedures, therefore the final effluent is expected to contain residual amounts of elemental chlorine or chlorine-based compounds. Limits on the concentration of TRC are specified to ensure that ambient water quality standards are maintained and that BPT technology is being applied to the discharge. Department licensing/permitting actions impose the more stringent of either a water quality-based or BPT-based limit.

The previous permitting action established a daily maximum water quality-based limit of 0.15 mg/L for TRC along with a 1/month monitoring frequency. Both are being carried forward in this permitting action. With a monthly average discharge flow limit of 0.090 MGD and dilution factors as determined above, end-of-pipe acute and chronic water quality-based concentration thresholds may be calculated as follows:

Acute (A) Criterion 0.019 mg/L	Chronic (C) Criterion 0.011 mg/L	A & C Dilution Factors 8.2:1 (Mod. A)	Calculated Acute Threshold 0.15 mg/L	Chronic Threshold 0.39 mg/L
0.017 mg/L	0,011 mg =	36.2:1 (C)	-	

The Department establishes a daily maximum BPT limitation for TRC of 1.0 mg/L for facilities that utilize elemental chlorine or chlorine-based compounds in their treatment processes. For facilities that must dechlorinate the effluent in order to consistently achieve compliance with water quality-based thresholds, the Department establishes daily maximum and monthly average BPT limits of 0.3 mg/L and 0.1 mg/L, respectively. The calculated acute water quality-based threshold of 0.15 mg/L is more stringent than the BPT-based standard of 0.3 mg/L. Therefore the water quality based limitation of 0.15 mg/L is being carried forward in this permitting action.

The Department reviewed 3 Discharge Monitoring Reports (DMRs) that were submitted for the period November 2009 – May 2014. A review of data indicates the following:

Total residual chlorine - Outfall #001 (Southern)

Total residual chiorn			
Value	Limit (mg/L)	Range (mg/L)	Average (mg/L)
Daily Maximum	0.15	<0.10 – 0.15	0.12

f. <u>pH</u>: The previous permitting action established a technology-based pH range limit of 6.0 - 8.5 standard units (SU) and a monitoring requirement of 1/Week. This permitting action is carrying forward the pH range limit of 6.0 to 8.5 SU, which is considered by the Department as a BPT standard for drinking water treatment facility.

A review of the DMR data for the period January 2006 – June 2009 indicates the permittee has been in compliance with the pH range limitation 100% of said period

g. Total Aluminum: The previous permitting action established water quality based monthly average mass and concentration limits for total aluminum of 3.1 mg/L and 2.3 lbs/day respectively, and a minimum monitoring frequency requirement of once per month. The basis for establishing aluminum limits is the presence of this metal in the final effluent resulting from the use of an aluminum sulfate coagulant for flocculation of suspended solids in the raw water. The USEPA's General Permit for drinking water treatment facilities in Maine, which was issued to several Maine facilities on or after January 9, 1995, contained a daily maximum concentration limit for aluminum of 5.0 mg/L. This limit was considered a BPT standard for drinking water treatment facility discharges in Maine and has been established in several MEPDES permits, including PIUD's, since the State received authorization to administer the NPDES permit program.

Department licensing/permitting actions impose the more stringent of either a water quality-based or BPT-based limit. 06-096 CMR 530(4)(C), states "The background concentration of specific chemicals must be included in all calculations using the following procedures. The Department may publish and periodically update a list of default background concentrations for specific pollutants on a regional, watershed or statewide basis. In doing so, the Department shall use data collected from reference sites that are measured at points not significantly affected by point and non-point discharges and best calculated to accurately represent ambient water quality conditions." "The Department shall use the same general methods as those in section 4(D) to determine background concentrations. For pollutants not listed by the Department, an assumed concentration of 10% of the applicable water quality criteria must be used in calculations." The Department has no information on the background levels of metals in the water column in the Presque Isle Stream. Therefore, a default background concentration of 10% of applicable water quality criteria is being used in the calculations of this permitting action. 06-096 CMR 530(4)(E), states "In allocating assimilative capacity for toxic pollutants, the Department shall hold a portion of the total capacity in an unallocated reserve to allow for new or changed discharges and non-point source contributions. The unallocated reserve must be reviewed and restored as necessary at

intervals of not more than five years. The water quality reserve must be not less than 15% of the total assimilative quantity." Therefore, the Department is reserving 15% of applicable water quality criteria used in the calculations of this permitting action.

Thus, end-of-pipe (EOP) aluminum concentration limit may be derived as follows:

Aluminum (Total):

Chronic AWQC = 87 ug/L Chronic dilution factor = 36.2:1

EOP concentration = [Dilution factor x $0.75 \times AWQC$] + $[0.25 \times AWQC]$

 $EOP = [36.2 \times 0.75 \times 0.087 \text{ mg/L}] + [0.25 \times 0.087 \text{ mg/L}] = 2.4 \text{ mg/L}$

Based on a permitted flow of 0.090 MGD, EOP mass limits are as follows:

Daily Max Mass Limit = (2.4 mg/L)(8.34)(0.090 MGD) = 1.8 lbs/day

In accordance with 38 M.R.S.A. 464(4)(k), this permitting action is eliminating the daily maximum concentration limit for ammonia.

This permitting action is carrying forward the water quality based mass limit of 1.8 lbs./day as calculated above. This permitting action is also carrying forward a minimum monitoring frequency requirement of once per month.

The Department reviewed 3 Discharge Monitoring Reports (DMRs) that were submitted for the period November 2009 – May 2014. A review of data indicates the following:

Total aluminum concentration - Outfall #001 (Southern)

Value	Limit (mg/L)	Range (mg/L)	Average (mg/L)
Monthly Average	3.1	0.3 - 0.4	0.4

Total aluminum mass - Outfall #001 (Southern)

Value	Limit (lbs/day)	Range (lbs/day)	Average (lbs/day)
Monthly Average	1.8	0.0 - 0.0	0.0

7. DISCHARGE IMPACT ON RECEIVING WATER QUALITY

As permitted, the Department has determined the existing water uses will be maintained and protected and the discharge will not cause or contribute to the failure of the water body to meet standards for Class B classification.

8. PUBLIC COMMENTS

Public notice of this application was made in the <u>Star Herald</u> newspaper on or about <u>July 30</u>, <u>2014</u>. The Department receives public comments on an application until the date a final agency action is taken on the application. Those persons receiving copies of draft permits must have at least 30 days in which to submit comments on the draft or to request a public hearing, pursuant to *Application Processing Procedures for Waste Discharge Licenses*, 06-096 CMR 522 (effective January 12, 2001).

9. DEPARTMENT CONTACTS

Additional information concerning this permitting action may be obtained from, and written comments sent to:


Yvette Meunier
Division of Water Quality Management
Bureau of Land & Water Quality
Department of Environmental Protection
17 State House Station
Augusta, Maine 04333-0017 Telephone: (207) 215-1579

e-mail: yvette.meunier@maine.gov

10. RESPONSE TO COMMENTS

During the period of September 16, 2014 through the issuance of this permit, the Department solicited comments on the proposed draft Maine Pollutant Discharge Elimination System Permit to be issued to the Presque Isle Water District for the proposed discharge. The Department did not receive comments from the permittee, state or federal agencies or interested parties that resulted in any substantive change(s) in the terms and conditions of the permit. Therefore the Department has not prepared a Response to Comments. It is noted that minor typographical and grammatical errors identified in comments are not included in this section, but were corrected, where necessary, in the final permit.


ATTACHMENT A



Maine Department of Environmental Protection Division of Water Resource Regulation

September 23, 2004

ATTACHMENT B



STANDARD CONDITIONS APPLICABLE TO ALL PERMITS

CONTENTS

SECTION		TOPIC	PAGE
Α		GENERAL PROVISIONS	
	1	General compliance	2
	2	Other materials	2
	3	Duty to Comply	2
	4	Duty to provide information	2
	5	Permit actions	2
	6	Reopener clause	2
	7	Oil and hazardous substances	2 2 2 2 3 3
	8	Property rights	3
	9	Confidentiality	3
	10	Duty to reapply	3
	11	Other laws	3
	12	Inspection and entry	3
В		OPERATION AND MAINTENANCE OF FACILITIES	
	1	General facility requirements	3
	2	Proper operation and maintenance	4
	3	Need to halt reduce not a defense	4
	4	Duty to mitigate	4
	5	Bypasses	4
	6	Upsets	5
С		MONITORING AND RECORDS	
	1	General requirements	6
	2	Representative sampling	6
	3	Monitoring and records	6
D		REPORTING REQUIREMENTS	
	1	Reporting requirements	7
	2	Signatory requirement	8
	3	Availability of reports	8
	4	Existing manufacturing, commercial, mining, and silvicultural dischargers	8
	5	Publicly owned treatment works	9
Е		OTHER PROVISIONS	
	1	Emergency action - power failure	9
	2	Spill prevention	10
	3	Removed substances	10
	4	Connection to municipal sewer	10
F		DEFINITIONS	10

STANDARD CONDITIONS APPLICABLE TO ALL PERMITS

A. GENERAL PROVISIONS

- 1. General compliance. All discharges shall be consistent with the terms and conditions of this permit; any changes in production capacity or process modifications which result in changes in the quantity or the characteristics of the discharge must be authorized by an additional license or by modifications of this permit; it shall be a violation of the terms and conditions of this permit to discharge any pollutant not identified and authorized herein or to discharge in excess of the rates or quantities authorized herein or to violate any other conditions of this permit.
- 2. Other materials. Other materials ordinarily produced or used in the operation of this facility, which have been specifically identified in the application, may be discharged at the maximum frequency and maximum level identified in the application, provided:
 - (a) They are not
 - (i) Designated as toxic or hazardous under the provisions of Sections 307 and 311, respectively, of the Federal Water Pollution Control Act; Title 38, Section 420, Maine Revised Statutes; or other applicable State Law; or
 - (ii) Known to be hazardous or toxic by the licensee.
 - (b) The discharge of such materials will not violate applicable water quality standards.
- 3. Duty to comply. The permittee must comply with all conditions of this permit. Any permit noncompliance constitutes a violation of State law and the Clean Water Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or modification; or denial of a permit renewal application.
 - (a) The permittee shall comply with effluent standards or prohibitions established under section 307(a) of the Clean Water Act, and 38 MRSA, §420 or Chapter 530.5 for toxic pollutants within the time provided in the regulations that establish these standards or prohibitions, even if the permit has not yet been modified to incorporate the requirement.
 - (b) Any person who violates any provision of the laws administered by the Department, including without limitation, a violation of the terms of any order, rule license, permit, approval or decision of the Board or Commissioner is subject to the penalties set forth in 38 MRSA, §349.
- 4. Duty to provide information. The permittee shall furnish to the Department, within a reasonable time, any information which the Department may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit or to determine compliance with this permit. The permittee shall also furnish to the Department upon request, copies of records required to be kept by this permit.
- 5. Permit actions. This permit may be modified, revoked and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition.
- 6. Reopener clause. The Department reserves the right to make appropriate revisions to this permit in order to establish any appropriate effluent limitations, schedule of compliance or other provisions which may be authorized under 38 MRSA, §414-A(5).

STANDARD CONDITIONS APPLICABLE TO ALL PERMITS

- 7. Oil and hazardous substances. Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities or penalties to which the permittee is or may be subject under section 311 of the Federal Clean Water Act; section 106 of the Federal Comprehensive Environmental Response, Compensation and Liability Act of 1980; or 38 MRSA §§ 1301, et. seq.
- 8. Property rights. This permit does not convey any property rights of any sort, or any exclusive privilege.
- 9. Confidentiality of records. 38 MRSA §414(6) reads as follows. "Any records, reports or information obtained under this subchapter is available to the public, except that upon a showing satisfactory to the department by any person that any records, reports or information, or particular part or any record, report or information, other than the names and addresses of applicants, license applications, licenses, and effluent data, to which the department has access under this subchapter would, if made public, divulge methods or processes that are entitled to protection as trade secrets, these records, reports or information must be confidential and not available for public inspection or examination. Any records, reports or information may be disclosed to employees or authorized representatives of the State or the United States concerned with carrying out this subchapter or any applicable federal law, and to any party to a hearing held under this section on terms the commissioner may prescribe in order to protect these confidential records, reports and information, as long as this disclosure is material and relevant to any issue under consideration by the department."
- 10. Duty to reapply. If the permittee wishes to continue an activity regulated by this permit after the expiration date of this permit, the permittee must apply for and obtain a new permit.
- 11. Other laws. The issuance of this permit does not authorize any injury to persons or property or invasion of other property rights, nor does it relieve the permittee if its obligation to comply with other applicable Federal, State or local laws and regulations.
- 12. Inspection and entry. The permittee shall allow the Department, or an authorized representative (including an authorized contractor acting as a representative of the EPA Administrator), upon presentation of credentials and other documents as may be required by law, to:
 - (a) Enter upon the permittee's premises where a regulated facility or activity is located or conducted, or where records must be kept under the conditions of this permit;
 - (b) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
 - (c) Inspect at reasonable times any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this permit; and
 - (d) Sample or monitor at reasonable times, for the purposes of assuring permit compliance or as otherwise authorized by the Clean Water Act, any substances or parameters at any location.

B. OPERATION AND MAINTENACE OF FACILITIES

- 1. General facility requirements.
 - (a) The permittee shall collect all waste flows designated by the Department as requiring treatment and discharge them into an approved waste treatment facility in such a manner as to

STANDARD CONDITIONS APPLICABLE TO ALL PERMITS

maximize removal of pollutants unless authorization to the contrary is obtained from the Department.

(b) The permittee shall at all times maintain in good working order and operate at maximum efficiency all waste water collection, treatment and/or control facilities.

(c) All necessary waste treatment facilities will be installed and operational prior to the discharge of any wastewaters.

(d) Final plans and specifications must be submitted to the Department for review prior to the construction or modification of any treatment facilities.

(e) The permittee shall install flow measuring facilities of a design approved by the Department.

- (f) The permittee must provide an outfall of a design approved by the Department which is placed in the receiving waters in such a manner that the maximum mixing and dispersion of the wastewaters will be achieved as rapidly as possible.
- 2. Proper operation and maintenance. The permittee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the permittee to achieve compliance with the conditions of this permit. Proper operation and maintenance also includes adequate laboratory controls and appropriate quality assurance procedures. This provision requires the operation of back-up or auxiliary facilities or similar systems which are installed by a permittee only when the operation is necessary to achieve compliance with the conditions of the permit.
- 3. Need to halt or reduce activity not a defense. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.
- 4. Duty to mitigate. The permittee shall take all reasonable steps to minimize or prevent any discharge or sludge use or disposal in violation of this permit which has a reasonable likelihood of adversely affecting human health or the environment.

5. Bypasses.

- (a) Definitions.
 - (i) Bypass means the intentional diversion of waste streams from any portion of a treatment facility.
 - (ii) Severe property damage means substantial physical damage to property, damage to the treatment facilities which causes them to become inoperable, or substantial and permanent loss of natural resources which can reasonably be expected to occur in the absence of a bypass. Severe property damage does not mean economic loss caused by delays in production.
- (b) Bypass not exceeding limitations. The permittee may allow any bypass to occur which does not cause effluent limitations to be exceeded, but only if it also is for essential maintenance to assure efficient operation. These bypasses are not subject to the provisions of paragraphs (c) and (d) of this section.
- (c) Notice.
 - (i) Anticipated bypass. If the permittee knows in advance of the need for a bypass, it shall submit prior notice, if possible at least ten days before the date of the bypass.

STANDARD CONDITIONS APPLICABLE TO ALL PERMITS

(ii) Unanticipated bypass. The permittee shall submit notice of an unanticipated bypass as required in paragraph D(1)(f), below. (24-hour notice).

(d) Prohibition of bypass.

- (i) Bypass is prohibited, and the Department may take enforcement action against a permittee for bypass, unless:
 - (A) Bypass was unavoidable to prevent loss of life, personal injury, or severe property damage;
 - (B) There were no feasible alternatives to the bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, or maintenance during normal periods of equipment downtime. This condition is not satisfied if adequate back-up equipment should have been installed in the exercise of reasonable engineering judgment to prevent a bypass which occurred during normal periods of equipment downtime or preventive maintenance; and
 - (C) The permittee submitted notices as required under paragraph (c) of this section.
- (ii) The Department may approve an anticipated bypass, after considering its adverse effects, if the Department determines that it will meet the three conditions listed above in paragraph (d)(i) of this section.

6. Upsets.

- (a) Definition. Upset means an exceptional incident in which there is unintentional and temporary noncompliance with technology based permit effluent limitations because of factors beyond the reasonable control of the permittee. An upset does not include noncompliance to the extent caused by operational error, improperly designed treatment facilities, inadequate treatment facilities, lack of preventive maintenance, or careless or improper operation.
- (b) Effect of an upset. An upset constitutes an affirmative defense to an action brought for noncompliance with such technology based permit effluent limitations if the requirements of paragraph (c) of this section are met. No determination made during administrative review of claims that noncompliance was caused by upset, and before an action for noncompliance, is final administrative action subject to judicial review.
- (c) Conditions necessary for a demonstration of upset. A permittee who wishes to establish the affirmative defense of upset shall demonstrate, through properly signed, contemporaneous operating logs, or other relevant evidence that:
 - (i) An upset occurred and that the permittee can identify the cause(s) of the upset;
 - (ii) The permitted facility was at the time being properly operated; and
 - (iii) The permittee submitted notice of the upset as required in paragraph D(1)(f), below. (24 hour notice).
 - (iv) The permittee complied with any remedial measures required under paragraph B(4).
- (d) Burden of proof. In any enforcement proceeding the permittee seeking to establish the occurrence of an upset has the burden of proof.

STANDARD CONDITIONS APPLICABLE TO ALL PERMITS

C. MONITORING AND RECORDS

- 1. General Requirements. This permit shall be subject to such monitoring requirements as may be reasonably required by the Department including the installation, use and maintenance of monitoring equipment or methods (including, where appropriate, biological monitoring methods). The permittee shall provide the Department with periodic reports on the proper Department reporting form of monitoring results obtained pursuant to the monitoring requirements contained herein.
- 2. Representative sampling. Samples and measurements taken as required herein shall be representative of the volume and nature of the monitored discharge. If effluent limitations are based wholly or partially on quantities of a product processed, the permittee shall ensure samples are representative of times when production is taking place. Where discharge monitoring is required when production is less than 50%, the resulting data shall be reported as a daily measurement but not included in computation of averages, unless specifically authorized by the Department.

3. Monitoring and records.

- (a) Samples and measurements taken for the purpose of monitoring shall be representative of the monitored activity.
- (b) Except for records of monitoring information required by this permit related to the permittee's sewage sludge use and disposal activities, which shall be retained for a period of at least five years, the permittee shall retain records of all monitoring information, including all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by this permit, and records of all data used to complete the application for this permit, for a period of at least 3 years from the date of the sample, measurement, report or application. This period may be extended by request of the Department at any time.
- (c) Records of monitoring information shall include:
 - (i) The date, exact place, and time of sampling or measurements;
 - (ii) The individual(s) who performed the sampling or measurements;
 - (iii) The date(s) analyses were performed;
 - (iv) The individual(s) who performed the analyses;
 - (v) The analytical techniques or methods used; and
 - (vi) The results of such analyses.
- (d) Monitoring results must be conducted according to test procedures approved under 40 CFR part 136, unless other test procedures have been specified in the permit.
- (e) State law provides that any person who tampers with or renders inaccurate any monitoring devices or method required by any provision of law, or any order, rule license, permit approval or decision is subject to the penalties set forth in 38 MRSA, §349.

STANDARD CONDITIONS APPLICABLE TO ALL PERMITS

D. REPORTING REQUIREMENTS

1. Reporting requirements.

- (a) Planned changes. The permittee shall give notice to the Department as soon as possible of any planned physical alterations or additions to the permitted facility. Notice is required only when:
 - (i) The alteration or addition to a permitted facility may meet one of the criteria for determining whether a facility is a new source in 40 CFR 122.29(b); or
 - (ii) The alteration or addition could significantly change the nature or increase the quantity of pollutants discharged. This notification applies to pollutants which are subject neither to effluent limitations in the permit, nor to notification requirements under Section D(4).
 - (iii) The alteration or addition results in a significant change in the permittee's sludge use or disposal practices, and such alteration, addition, or change may justify the application of permit conditions that are different from or absent in the existing permit, including notification of additional use or disposal sites not reported during the permit application process or not reported pursuant to an approved land application plan;
- (b) Anticipated noncompliance. The permittee shall give advance notice to the Department of any planned changes in the permitted facility or activity which may result in noncompliance with permit requirements.
- (c) Transfers. This permit is not transferable to any person except upon application to and approval of the Department pursuant to 38 MRSA, § 344 and Chapters 2 and 522.
- (d) Monitoring reports. Monitoring results shall be reported at the intervals specified elsewhere in this permit.
 - (i) Monitoring results must be reported on a Discharge Monitoring Report (DMR) or forms provided or specified by the Department for reporting results of monitoring of sludge use or disposal practices.
 - (ii) If the permittee monitors any pollutant more frequently than required by the permit using test procedures approved under 40 CFR part 136 or as specified in the permit, the results of this monitoring shall be included in the calculation and reporting of the data submitted in the DMR or sludge reporting form specified by the Department.
 - (iii) Calculations for all limitations which require averaging of measurements shall utilize an arithmetic mean unless otherwise specified by the Department in the permit.
- (e) Compliance schedules. Reports of compliance or noncompliance with, or any progress reports on, interim and final requirements contained in any compliance schedule of this permit shall be submitted no later than 14 days following each schedule date.
- (f) Twenty-four hour reporting.
 - (i) The permittee shall report any noncompliance which may endanger health or the environment. Any information shall be provided orally within 24 hours from the time the permittee becomes aware of the circumstances. A written submission shall also be provided within 5 days of the time the permittee becomes aware of the circumstances. The written submission shall contain a description of the noncompliance and its cause; the period of noncompliance, including exact dates and times, and if the noncompliance

STANDARD CONDITIONS APPLICABLE TO ALL PERMITS

has not been corrected, the anticipated time it is expected to continue; and steps taken or planned to reduce, eliminate, and prevent reoccurrence of the noncompliance.

- (ii) The following shall be included as information which must be reported within 24 hours under this paragraph.
 - (A) Any unanticipated bypass which exceeds any effluent limitation in the permit.

(B) Any upset which exceeds any effluent limitation in the permit.

- (C) Violation of a maximum daily discharge limitation for any of the pollutants listed by the Department in the permit to be reported within 24 hours.
- (iii) The Department may waive the written report on a case-by-case basis for reports under paragraph (f)(ii) of this section if the oral report has been received within 24 hours.
- (g) Other noncompliance. The permittee shall report all instances of noncompliance not reported under paragraphs (d), (e), and (f) of this section, at the time monitoring reports are submitted. The reports shall contain the information listed in paragraph (f) of this section.
- (h) Other information. Where the permittee becomes aware that it failed to submit any relevant facts in a permit application, or submitted incorrect information in a permit application or in any report to the Department, it shall promptly submit such facts or information.
- 2. Signatory requirement. All applications, reports, or information submitted to the Department shall be signed and certified as required by Chapter 521, Section 5 of the Department's rules. State law provides that any person who knowingly makes any false statement, representation or certification in any application, record, report, plan or other document filed or required to be maintained by any order, rule, permit, approval or decision of the Board or Commissioner is subject to the penalties set forth in 38 MRSA, §349.
- 3. Availability of reports. Except for data determined to be confidential under A(9), above, all reports prepared in accordance with the terms of this permit shall be available for public inspection at the offices of the Department. As required by State law, effluent data shall not be considered confidential. Knowingly making any false statement on any such report may result in the imposition of criminal sanctions as provided by law.
- 4. Existing manufacturing, commercial, mining, and silvicultural dischargers. In addition to the reporting requirements under this Section, all existing manufacturing, commercial, mining, and silvicultural dischargers must notify the Department as soon as they know or have reason to believe:
 - (a) That any activity has occurred or will occur which would result in the discharge, on a routine or frequent basis, of any toxic pollutant which is not limited in the permit, if that discharge will exceed the highest of the following "notification levels":
 - (i) One hundred micrograms per liter (100 ug/l);
 - (ii) Two hundred micrograms per liter (200 ug/l) for acrolein and acrylonitrile; five hundred micrograms per liter (500 ug/l) for 2,4-dinitrophenol and for 2-methyl-4,6-dinitrophenol; and one milligram per liter (1 mg/l) for antimony;
 - (iii) Five (5) times the maximum concentration value reported for that pollutant in the permit application in accordance with Chapter 521 Section 4(g)(7); or
 - (iv) The level established by the Department in accordance with Chapter 523 Section 5(f).

STANDARD CONDITIONS APPLICABLE TO ALL PERMITS

- (b) That any activity has occurred or will occur which would result in any discharge, on a non-routine or infrequent basis, of a toxic pollutant which is not limited in the permit, if that discharge will exceed the highest of the following "notification levels":
 - (i) Five hundred micrograms per liter (500 ug/l);
 - (ii) One milligram per liter (1 mg/l) for antimony;
 - (iii) Ten (10) times the maximum concentration value reported for that pollutant in the permit application in accordance with Chapter 521 Section 4(g)(7); or
 - (iv) The level established by the Department in accordance with Chapter 523 Section 5(f).

5. Publicly owned treatment works.

- (a) All POTWs must provide adequate notice to the Department of the following:
 - (i) Any new introduction of pollutants into the POTW from an indirect discharger which would be subject to section 301 or 306 of CWA or Chapter 528 if it were directly discharging those pollutants.
 - (ii) Any substantial change in the volume or character of pollutants being introduced into that POTW by a source introducing pollutants into the POTW at the time of issuance of the permit.
 - (iii) For purposes of this paragraph, adequate notice shall include information on (A) the quality and quantity of effluent introduced into the POTW, and (B) any anticipated impact of the change on the quantity or quality of effluent to be discharged from the POTW.
- (b) When the effluent discharged by a POTW for a period of three consecutive months exceeds 80 percent of the permitted flow, the permittee shall submit to the Department a projection of loadings up to the time when the design capacity of the treatment facility will be reached, and a program for maintaining satisfactory treatment levels consistent with approved water quality management plans.

E. OTHER REQUIREMENTS

- 1. Emergency action power failure. Within thirty days after the effective date of this permit, the permittee shall notify the Department of facilities and plans to be used in the event the primary source of power to its wastewater pumping and treatment facilities fails as follows.
 - (a) For municipal sources. During power failure, all wastewaters which are normally treated shall receive a minimum of primary treatment and disinfection. Unless otherwise approved, alternate power supplies shall be provided for pumping stations and treatment facilities. Alternate power supplies shall be on-site generating units or an outside power source which is separate and independent from sources used for normal operation of the wastewater facilities.
 - (b) For industrial and commercial sources. The permittee shall either maintain an alternative power source sufficient to operate the wastewater pumping and treatment facilities or halt, reduce or otherwise control production and or all discharges upon reduction or loss of power to the wastewater pumping or treatment facilities.

STANDARD CONDITIONS APPLICABLE TO ALL PERMITS

- 2. Spill prevention. (applicable only to industrial sources) Within six months of the effective date of this permit, the permittee shall submit to the Department for review and approval, with or without conditions, a spill prevention plan. The plan shall delineate methods and measures to be taken to prevent and or contain any spills of pulp, chemicals, oils or other contaminates and shall specify means of disposal and or treatment to be used.
- 3. **Removed substances.** Solids, sludges trash rack cleanings, filter backwash, or other pollutants removed from or resulting from the treatment or control of waste waters shall be disposed of in a manner approved by the Department.
- 4. Connection to municipal sewer. (applicable only to industrial and commercial sources) All wastewaters designated by the Department as treatable in a municipal treatment system will be cosigned to that system when it is available. This permit will expire 90 days after the municipal treatment facility becomes available, unless this time is extended by the Department in writing.
- **F. DEFINITIONS.** For the purposes of this permit, the following definitions shall apply. Other definitions applicable to this permit may be found in Chapters 520 through 529 of the Department's rules

Average means the arithmetic mean of values taken at the frequency required for each parameter over the specified period. For bacteria, the average shall be the geometric mean.

Average monthly discharge limitation means the highest allowable average of daily discharges over a calendar month, calculated as the sum of all daily discharges measured during a calendar month divided by the number of daily discharges measured during that month. Except, however, bacteriological tests may be calculated as a geometric mean.

Average weekly discharge limitation means the highest allowable average of daily discharges over a calendar week, calculated as the sum of all daily discharges measured during a calendar week divided by the number of daily discharges measured during that week.

Best management practices ("BMPs") means schedules of activities, prohibitions of practices, maintenance procedures, and other management practices to prevent or reduce the pollution of waters of the State. BMPs also include treatment requirements, operating procedures, and practices to control plant site runoff, spillage or leaks, sludge or waste disposal, or drainage from raw material storage.

Composite sample means a sample consisting of a minimum of eight grab samples collected at equal intervals during a 24 hour period (or a lesser period as specified in the section on monitoring and reporting) and combined proportional to the flow over that same time period.

Continuous discharge means a discharge which occurs without interruption throughout the operating hours of the facility, except for infrequent shutdowns for maintenance, process changes, or other similar activities.

Daily discharge means the discharge of a pollutant measured during a calendar day or any 24-hour period that reasonably represents the calendar day for purposes of sampling. For pollutants with limitations expressed in units of mass, the daily discharge is calculated as the total mass of the pollutant discharged over the day. For pollutants with limitations expressed in other units of measurement, the daily discharge is calculated as the average measurement of the pollutant over the day.

STANDARD CONDITIONS APPLICABLE TO ALL PERMITS

Discharge Monitoring Report ("DMR") means the EPA uniform national form, including any subsequent additions, revisions, or modifications for the reporting of self-monitoring results by permittees. DMRs must be used by approved States as well as by EPA. EPA will supply DMRs to any approved State upon request. The EPA national forms may be modified to substitute the State Agency name, address, logo, and other similar information, as appropriate, in place of EPA's.

Flow weighted composite sample means a composite sample consisting of a mixture of aliquots collected at a constant time interval, where the volume of each aliquot is proportional to the flow rate of the discharge.

Grab sample means an individual sample collected in a period of less than 15 minutes.

Interference means a Discharge which, alone or in conjunction with a discharge or discharges from other sources, both:

- (1) Inhibits or disrupts the POTW, its treatment processes or operations, or its sludge processes, use or disposal; and
- (2) Therefore is a cause of a violation of any requirement of the POTW's NPDES permit (including an increase in the magnitude or duration of a violation) or of the prevention of sewage sludge use or disposal in compliance with the following statutory provisions and regulations or permits issued thereunder (or more stringent State or local regulations): Section 405 of the Clean Water Act, the Solid Waste Disposal Act (SWDA) (including title II, more commonly referred to as the Resource Conservation and Recovery Act (RCRA), and including State regulations contained in any State sludge management plan prepared pursuant to subtitle D of the SWDA), the Clean Air Act, the Toxic Substances Control Act, and the Marine Protection, Research and Sanctuaries Act.

Maximum daily discharge limitation means the highest allowable daily discharge.

New source means any building, structure, facility, or installation from which there is or may be a discharge of pollutants, the construction of which commenced:

- (a) After promulgation of standards of performance under section 306 of CWA which are applicable to such source, or
- (b) After proposal of standards of performance in accordance with section 306 of CWA which are applicable to such source, but only if the standards are promulgated in accordance with section 306 within 120 days of their proposal.

Pass through means a discharge which exits the POTW into waters of the State in quantities or concentrations which, alone or in conjunction with a discharge or discharges from other sources, is a cause of a violation of any requirement of the POTW's NPDES permit (including an increase in the magnitude or duration of a violation).

Permit means an authorization, license, or equivalent control document issued by EPA or an approved State to implement the requirements of 40 CFR parts 122, 123 and 124. Permit includes an NPDES general permit (Chapter 529). Permit does not include any permit which has not yet been the subject of final agency action, such as a draft permit or a proposed permit.

Person means an individual, firm, corporation, municipality, quasi-municipal corporation, state agency, federal agency or other legal entity.

STANDARD CONDITIONS APPLICABLE TO ALL PERMITS

Point source means any discernible, confined and discrete conveyance, including, but not limited to, any pipe, ditch, channel, tunnel, conduit, well, discrete fissure, container, rolling stock, concentrated animal feeding operation or vessel or other floating craft, from which pollutants are or may be discharged.

Pollutant means dredged spoil, solid waste, junk, incinerator residue, sewage, refuse, effluent, garbage, sewage sludge, munitions, chemicals, biological or radiological materials, oil, petroleum products or byproducts, heat, wrecked or discarded equipment, rock, sand, dirt and industrial, municipal, domestic, commercial or agricultural wastes of any kind.

Process wastewater means any water which, during manufacturing or processing, comes into direct contact with or results from the production or use of any raw material, intermediate product, finished product, byproduct, or waste product.

Publicly owned treatment works ("POTW") means any facility for the treatment of pollutants owned by the State or any political subdivision thereof, any municipality, district, quasi-municipal corporation or other public entity.

Septage means, for the purposes of this permit, any waste, refuse, effluent sludge or other material removed from a septic tank, cesspool, vault privy or similar source which concentrates wastes or to which chemicals have been added. Septage does not include wastes from a holding tank.

Time weighted composite means a composite sample consisting of a mixture of equal volume aliquots collected over a constant time interval.

Toxic pollutant includes any pollutant listed as toxic under section 307(a)(1) or, in the case of sludge use or disposal practices, any pollutant identified in regulations implementing section 405(d) of the CWA. Toxic pollutant also includes those substances or combination of substances, including disease causing agents, which after discharge or upon exposure, ingestion, inhalation or assimilation into any organism, including humans either directly through the environment or indirectly through ingestion through food chains, will, on the basis of information available to the board either alone or in combination with other substances already in the receiving waters or the discharge, cause death, disease, abnormalities, cancer, genetic mutations, physiological malfunctions, including malfunctions in reproduction, or physical deformations in such organism or their offspring.

Wetlands means those areas that are inundated or saturated by surface or ground water at a frequency and duration sufficient to support, and that under normal circumstances do support, a prevalence of vegetation typically adapted for life in saturated soil conditions. Wetlands generally include swamps, marshes, bogs, and similar areas.

Whole effluent toxicity means the aggregate toxic effect of an effluent measured directly by a toxicity test.



DEP INFORMATION SHEET

Appealing a Department Licensing Decision

Dated: March 2012 Contact: (207) 287-2811

SUMMARY

There are two methods available to an aggrieved person seeking to appeal a licensing decision made by the Department of Environmental Protection's ("DEP") Commissioner: (1) in an administrative process before the Board of Environmental Protection ("Board"); or (2) in a judicial process before Maine's Superior Court. An aggrieved person seeking review of a licensing decision over which the Board had original jurisdiction may seek judicial review in Maine's Superior Court.

A judicial appeal of final action by the Commissioner or the Board regarding an application for an expedited wind energy development (35-A M.R.S.A. § 3451(4)) or a general permit for an offshore wind energy demonstration project (38 M.R.S.A. § 480-HH(1) or a general permit for a tidal energy demonstration project (38 M.R.S.A. § 636-A) must be taken to the Supreme Judicial Court sitting as the Law Court.

This INFORMATION SHEET, in conjunction with a review of the statutory and regulatory provisions referred to herein, can help a person to understand his or her rights and obligations in filing an administrative or judicial appeal.

I. ADMINISTRATIVE APPEALS TO THE BOARD

LEGAL REFERENCES

The laws concerning the DEP's Organization and Powers, 38 M.R.S.A. §§ 341-D(4) & 346, the Maine Administrative Procedure Act, 5 M.R.S.A. § 11001, and the DEP's Rules Concerning the Processing of Applications and Other Administrative Matters ("Chapter 2"), 06-096 CMR 2 (April 1, 2003).

HOW LONG YOU HAVE TO SUBMIT AN APPEAL TO THE BOARD

The Board must receive a written appeal within 30 days of the date on which the Commissioner's decision was filed with the Board. Appeals filed after 30 calendar days of the date on which the Commissioner's decision was filed with the Board will be rejected.

HOW TO SUBMIT AN APPEAL TO THE BOARD

Signed original appeal documents must be sent to: Chair, Board of Environmental Protection, c/o Department of Environmental Protection, 17 State House Station, Augusta, ME 04333-0017; faxes are acceptable for purposes of meeting the deadline when followed by the Board's receipt of mailed original documents within five (5) working days. Receipt on a particular day must be by 5:00 PM at DEP's offices in Augusta; materials received after 5:00 PM are not considered received until the following day. The person appealing a licensing decision must also send the DEP's Commissioner a copy of the appeal documents and if the person appealing is not the applicant in the license proceeding at issue the applicant must also be sent a copy of the appeal documents. All of the information listed in the next section must be submitted at the time the appeal is filed. Only the extraordinary circumstances described at the end of that section will justify evidence not in the DEP's record at the time of decision being added to the record for consideration by the Board as part of an appeal.

WHAT YOUR APPEAL PAPERWORK MUST CONTAIN

Appeal materials must contain the following information at the time submitted:

OCF/90-1/r95/r98/r99/r00/r04/r12

- 1. Aggrieved Status. The appeal must explain how the person filing the appeal has standing to maintain an appeal. This requires an explanation of how the person filing the appeal may suffer a particularized injury as a result of the Commissioner's decision.
- 2. The findings, conclusions or conditions objected to or believed to be in error. Specific references and facts regarding the appellant's issues with the decision must be provided in the notice of appeal.
- 3. The basis of the objections or challenge. If possible, specific regulations, statutes or other facts should be referenced. This may include citing omissions of relevant requirements, and errors believed to have been made in interpretations, conclusions, and relevant requirements.
- 4. The remedy sought. This can range from reversal of the Commissioner's decision on the license or permit to changes in specific permit conditions.
- 5. All the matters to be contested. The Board will limit its consideration to those arguments specifically raised in the written notice of appeal.
- 6. Request for hearing. The Board will hear presentations on appeals at its regularly scheduled meetings, unless a public hearing on the appeal is requested and granted. A request for public hearing on an appeal must be filed as part of the notice of appeal.
- 7. New or additional evidence to be offered. The Board may allow new or additional evidence, referred to as supplemental evidence, to be considered by the Board in an appeal only when the evidence is relevant and material and that the person seeking to add information to the record can show due diligence in bringing the evidence to the DEP's attention at the earliest possible time in the licensing process or that the evidence itself is newly discovered and could not have been presented earlier in the process. Specific requirements for additional evidence are found in Chapter 2.

OTHER CONSIDERATIONS IN APPEALING A DECISION TO THE BOARD

- Be familiar with all relevant material in the DEP record. A license application file is public
 information, subject to any applicable statutory exceptions, made easily accessible by DEP. Upon
 request, the DEP will make the material available during normal working hours, provide space to
 review the file, and provide opportunity for photocopying materials. There is a charge for copies or
 copying services.
- 2. Be familiar with the regulations and laws under which the application was processed, and the procedural rules governing your appeal. DEP staff will provide this information on request and answer questions regarding applicable requirements.
- 3. The filing of an appeal does not operate as a stay to any decision. If a license has been granted and it has been appealed the license normally remains in effect pending the processing of the appeal. A license holder may proceed with a project pending the outcome of an appeal but the license holder runs the risk of the decision being reversed or modified as a result of the appeal.

WHAT TO EXPECT ONCE YOU FILE A TIMELY APPEAL WITH THE BOARD

The Board will formally acknowledge receipt of an appeal, including the name of the DEP project manager assigned to the specific appeal. The notice of appeal, any materials accepted by the Board Chair as supplementary evidence, and any materials submitted in response to the appeal will be sent to Board members with a recommendation from DEP staff. Persons filing appeals and interested persons are notified in advance of the date set for Board consideration of an appeal or request for public hearing. With or without holding a public hearing, the Board may affirm, amend, or reverse a Commissioner decision or remand the matter to the Commissioner for further proceedings. The Board will notify the appellant, a license holder, and interested persons of its decision.

II. JUDICIAL APPEALS

Maine law generally allows aggrieved persons to appeal final Commissioner or Board licensing decisions to Maine's Superior Court, see 38 M.R.S.A. § 346(1); 06-096 CMR 2; 5 M.R.S.A. § 11001; & M.R. Civ. P 80C. A party's appeal must be filed with the Superior Court within 30 days of receipt of notice of the Board's or the Commissioner's decision. For any other person, an appeal must be filed within 40 days of the date the decision was rendered. Failure to file a timely appeal will result in the Board's or the Commissioner's decision becoming final.

An appeal to court of a license decision regarding an expedited wind energy development, a general permit for an offshore wind energy demonstration project, or a general permit for a tidal energy demonstration project may only be taken directly to the Maine Supreme Judicial Court. See 38 M.R.S.A. § 346(4).

Maine's Administrative Procedure Act, DEP statutes governing a particular matter, and the Maine Rules of Civil Procedure must be consulted for the substantive and procedural details applicable to judicial appeals.

ADDITIONAL INFORMATION

If you have questions or need additional information on the appeal process, for administrative appeals contact the Board's Executive Analyst at (207) 287-2452 or for judicial appeals contact the court clerk's office in which your appeal will be filed.

Note: The DEP provides this INFORMATION SHEET for general guidance only; it is not intended for use as a legal reference. Maine law governs an appellant's rights.