

State of Vermont
Department of Environmental Conservation
Wastewater Management Division
103 South Main St – The Sewing Bldg
Waterbury VT05671-0405
www.anr.state.vt.us/dec/ww/wwmd.cfm

[phone] 802-241-3822 [fax] 802-241-2596 Agency of Natural Resources

November 18, 2011

Thomas F Keefe Global Companies, LLC 2 Flynn Ave Burlington, VT 05401

Re: Final Discharge Permit #3-1239

Dear Mr Keefe:

Enclosed is your copy of the above referenced permit, which I have signed for the Commissioner of the Department of Environmental Conservation. Please read the permit carefully and familiarize yourself with all its terms and conditions. Your attention is particularly directed to those conditions which may require written responses by certain dates.

If you have any questions concerning your permit, please contact Carol Carpenter at 338-4832.

Sincerely,

Christine Thompson, Director

Enclosure



# AGENCY OF NATURAL RESOURCES DEPARTMENT OF ENVIRONMENTAL CONSERVATION WASTEWATER MANAGEMENT DIVISION 103 SOUTH MAIN STREET, - THE SEWING BUILDING WATERBURY, VERMONT 05671-0405

Permit No. 3-1239 Project ID No. EJ95-0251 NPDES No. VT0000353

## DISCHARGE PERMIT

In compliance with the provisions of the Vermont Water Pollution Control Act, as amended, (10 V.S.A. Chapter 47 §1251 et. seq), and the Federal Clean Water Act, as amended (33 U.S.C. § 1251 et. seq),

Global Companies LLC 2 Flynn Avenue Burlington, VT 05401

(hereinafter referred to as the "permittee") is authorized, by the Secretary, Agency of Natural Resources, to discharge from a facility located at:

Vermont Global Petroleum Services 2 Flynn Avenue Burlington, Vermont

To Lake Champlain, Class B at the point of discharge in accordance with effluent limitations, monitoring requirements, and other conditions set forth in Parts I, II, III hereof.

This permit shall become effective on the date of signing.

This permit and the authorization to discharge shall expire on September 30, 2016.

Signed this 18th day of Mormber, 2011.

David K Mears, Commissioner
Department of Environmental Conservation

By

Christine Thompson, Director Wastewater Management Division

Polynuclear Aromatic Hydrocarbons (PAH) (5)

#### PART I

# A. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS

Until September 30, 2016, the permittee is authorized to discharge from outfall serial number S/N 001: Petroleum contaminated stormwater after treatment via an oil/water separator and hydrostatic test water. Such discharges shall be limited and monitored by the permittee as

specified below: **Monitoring Requirements** Discharge Limitations Sample Measurement Effluent Monthly Daily Maximum Frequency Type Characteristic Average Flow (1) Estimate 144,000 gpd Each discharge Total Residual Chlorine Grab  $20 \mu g/l$ Each discharge (TRC) (2) Grab 71 µg/l 2 x monthly Benzene 2 x monthly Grab 15 mg/lOil & Grease **Total Suspended Solids** 2 x annually <sup>(4)</sup> Monitor only Grab (TSS) Between 6.5 and 8.5 Standard Units<sup>(3)</sup> 2 x annually <sup>(4)</sup> Grab Hq Benzene, Toluene, 2 x annually (4) Grab Ethylbenzene, and Monitor only Xylenes (BTEX) Methyl Tertiary-Butyl 2 x annually (4) Grab Monitor only Ether (MTBE) Total Petroleum 2 x annually (4) Monitor only Grab Hydrocarbons (TPH)

(1) The flow shall be controlled such that it does not exceed 100 gallons per minute. See also Special Condition I.B.1.

Monitor only

2 x annually (4)

Grab

- TRC monitoring is only required when municipal water is used as the source water for hydrostatic testing of tanks. See also Special Condition I.B.2.
- The pH shall not exceed the range of between 6.5 and 8.5 Standard Units at any time unless these values are exceeded as a result of natural causes.
- <sup>(4)</sup> Twice annual samples shall be collected in the months of May and October. If there is no discharge during the specified month, a sample shall be collected during the next month having a discharge.

Permit No. 3-1239 Page 3 of 14

The PAHs and their minimum level (ML) of reporting include: Benzo(a)anthracene (< 0.05 μg/l), Benzo(b)fluoranthene (< 0.1 μg/l), Chrysene (< 5.0 μg/l), Indeno(1,2,3-cd)pyrene (< 0.15 μg/l), Benzo(a)pyrene (< 2.0 μg/l), Benzo(k)fluoranthene (< 2.0 μg/l), Dibenzo(a,h)anthracene (< 0.1 μg/l), and Napthalene (< 0.2 μg/l). The lab sheets shall be submitted as an attachment to the discharge monitoring report form WR-43.

Samples taken in compliance with the monitoring requirements specified above shall be taken following treatment by the oil/water separator.

## B. SPECIAL CONDITIONS

## 1. Operational Controls

- a. The discharge shall not exceed 100 gallons per minute.
- b. Discharge from the facility shall occur only when qualified personnel are present on site to oversee the operation of the oil/water separator.
- c. When not in operation all valves to and from the oil/water separator shall be in the closed position.
- d. The dates and approximate duration of the discharge shall be recorded on the Discharge Monitoring Report (Form WR-43).

# 2. Hydrostatic Test Water Discharges

Tanks being hydrostatically tested shall be clean of product, all construction debris, including sandblasting grit, prior to testing. Hydrostatic test water shall be treated through the oil/water separator prior to discharge to Lake Champlain. The source water may be either from Lake Champlain and/or municipal water.

If municipal water is used as the source water, the water shall not be discharged unless the total residual chlorine is  $\leq 20 \ \mu g/l$ .

The water must be controlled to prevent it from exceeding the maximum design flow rate (100 gpm) of the oil/water separator.

The date(s) the testing occurred, the source water, the volume discharged, and the chlorine residual (if applicable) shall be submitted as an attachment to that month's Discharge Monitoring Report (Form WR-43).

# 3. Best Management Practices (BMPs)

The permittee shall implement a BMP plan which, at a minimum, shall include:

a. The Spill Prevention, Control, and Countermeasure Plan developed for this facility pursuant to Section 311 of the Clean Water Act and as certified on November 1, 2004, or as amended and certified thereafter, is hereby incorporated as part of the BMP plan.

Permit No. 3-1239 Page 4 of 14

b. Tank Bottom Water – water which is drawn off the bottom of the storage tanks – is not covered under this permit.

- c. Any waste petroleum product generated or collected as the result of treatment, spills, or any other activity at this site shall not be discharged, and if transported off site, shall be managed in accordance with Vermont Hazardous Waste Management Regulations.
- d. If the BMP plan proves ineffective in preventing the release of significant amounts of hazardous or toxic pollutants to waters of the State, then the Agency may reopen and amend the permit.
- 4. In order to discharge contaminated water from the truck transfer area (loading rack), the permittee shall design and construct an Agency approved treatment system for contaminated stormwater collected in the truck transfer area. The treatment system must be capable of meeting the terms and conditions of this permit. Should the permittee decide to pursue the discharge from the truck transfer area, the permit may be reopened and amended to include additional conditions specific to this wastestream.
- 5. This discharge shall not cause a violation of the water quality standards of the receiving water.

## C. REAPPLICATION

If the permittee desires to continue to discharge after the expiration date of this permit, the permittee shall apply on the application forms then in use at least 180 days before the permit expires.

Reapply for a Discharge Permit by: March 31, 2016.

#### D. OPERATING FEES

This discharge is subject to operating fees. The permittee shall submit the operating fees in accord with the procedures provided by the Secretary.

#### E. MONITORING AND REPORTING

## 1. Sampling and Analysis

The sampling, preservation, handling, and analytical methods used shall conform to regulations published pursuant to Section 304(g) of the Clean Water Act, under which such procedures may be required. Guidelines establishing these test procedures have been published in the Code of Federal Regulations, Title 40, Part 136 (Federal Register, Vol. 56, No. 195, July 1, 1999 or as amended).

If applicable, Escherichia coli shall be tested using one of the following methods:

a. "Most Probable Number" (MPN) method 9223B found in Standard Methods for the Examination of Water and Wastewater, 18th or subsequent approved

- edition(s). Premade formulations are available as Colilert and Colilert 18 from IDEXX Labs Inc., Westbrook, ME;
- b. EPA "membrane filtration" (MF) method 1603 using modified mTEC; or
- c. A single step <u>membrane filtration</u> (MF) method using mColiBlue 24 available from Hach Company, Loveland, CO.

Samples shall be representative of the volume and quality of effluent discharged over the sampling and reporting period. All samples are to be taken during normal operating hours. The permittee shall identify the effluent sampling location used for each discharge.

# 2. Reporting

The Permittee is required to submit monitoring results as specified on a Discharge Monitoring Report (Form WR-43). Reports are due on the 15th day of each month, beginning with the month following the effective date of this permit.

If, in any reporting period, there has been no discharge, the permittee must submit that information by the report due date.

Signed copies of these, and all other reports required herein, shall be submitted to the Secretary at the following address:

Agency of Natural Resources
Department of Environmental Conservation
Wastewater Management Division
103 South Main Street, The Sewing Building
Waterbury, Vermont 05671-0405

All reports shall be signed:

- a. In the case of corporations, by a principal executive officer of at least the level of vice president, or his/her duly authorized representative, if such representative is responsible for the overall operation of the facility from which the discharge described in the permit form originates;
- b. In the case of a partnership, by a general partner;
- c. In the case of a sole proprietorship, by the proprietor;
- d. In the case of a municipal, State, or other public facility, by either a principal executive officer, ranking elected official, or other duly authorized employee.

# 3. Recording of Results

The permittee shall maintain records of all information resulting from any monitoring activities required including:

a. The exact place, date, and time of sampling;

- b. The dates and times the analyses were performed;
- c. The person(s) who performed the analyses;
- d. The analytical techniques and methods used including sample collection handling and preservation techniques;
- e. The results of all required analyses;
- f. The records of monitoring activities and results, including all instrumentation and calibration and maintenance records;
- g. The original calculation and data bench sheets of the operator who performed analysis of the influent or effluent pursuant to requirements of Section I.(A) of this permit.

The results of monitoring requirements shall be reported (in the units specified) on the Vermont reporting form WR-43 or other forms approved by the Secretary.

## 4. Additional Monitoring

If the permittee monitors any pollutant at the location(s) designated herein more frequently than required by this permit, using approved analytical methods as specified above, the results of such monitoring shall be included in the calculation and reporting of the values required in the Discharge Monitoring Report Form WR-43. Such increased frequency shall also be indicated.

#### PART II

## A. MANAGEMENT REQUIREMENTS

## 1. Facility Modification / Change in Discharge:

All discharges authorized herein shall be consistent with the terms and conditions of this permit. The discharge of any pollutant more frequently than, or at a level in excess of, that identified and authorized by this permit shall constitute a violation of the terms and conditions of this permit. Such a violation may result in the imposition of civil and/or criminal penalties as provided for in Section 1274 and 1275 of the Vermont Water Pollution Control Act. Any anticipated facility expansions, production increases, or process modifications which will result in new, different, or increased discharges of pollutants must be reported by submission of a new permit application or, if such changes will not violate the effluent limitations specified in this permit, by notice to the permit issuing authority of such changes. Following such notice, the permit may be modified to specify and limit any pollutants not previously limited.

## 2. Noncompliance Notification

In the event the permittee is unable to comply with any of the conditions of this permit due, among other reasons, to:

a. breakdown or maintenance of waste treatment equipment (biological and physical-chemical systems including, but not limited to, all pipes, transfer

pumps, compressors, collection ponds or tanks for the segregation of treated or untreated wastes, ion exchange columns, or carbon absorption units),

- b. accidents caused by human error or negligence, or
- c. other causes such as acts of nature,

the permittee shall notify the Secretary within 24 hours of becoming aware of such condition or by the next business day and shall provide the Secretary with the following information, in writing, within five (5) days:

- i. cause of non-compliance;
- ii. a description of the non-complying discharge including its impact upon the receiving water;
- iii. anticipated time the condition of non-compliance is expected to continue or, if such condition has been corrected, the duration of the period of non-compliance;
- iv. steps taken by the permittee to reduce and eliminate the non-complying discharge; and
- v. steps to be taken by the permittee to prevent recurrence of the condition of non-compliance.

## 3. Operation and Maintenance

All waste collection, control, treatment, and disposal facilities shall be operated in a manner consistent with the following:

- a. The permittee shall, at all times, maintain in good working order and operate as efficiently as possible all treatment or control facilities or systems installed or used by the permittee to achieve compliance with the terms and conditions of this permit.
- b. The permittee shall provide an adequate operating staff which is duly qualified to carry out the operation, maintenance, and testing functions required to insure compliance with the conditions of this permit; and
- c. The operation and maintenance of this facility shall be performed only by qualified personnel.

# 4. Quality Control

The permittee shall calibrate and perform maintenance procedures on all monitoring and analytical instrumentation at regular intervals to ensure accuracy of measurements, or shall ensure that both activities will be conducted.

Permit No. 3-1239 Page 8 of 14

The permittee shall keep records of these activities and shall provide such records upon request of the Secretary.

The permittee shall analyze any additional samples as may be required by the Agency of Natural Resources to ensure analytical quality control.

## 5. Bypass

The diversion or bypass of facilities, necessary to maintain compliance with the terms and conditions of this permit, is prohibited, except where authorized under terms and conditions of an emergency pollution permit issued pursuant to 10 V.S.A. Section 1268.

## 6. Duty to Mitigate

The permittee shall take all reasonable steps to minimize or prevent any adverse impact to waters of the State resulting from non-compliance with any condition specified in this permit, including accelerated or additional monitoring as necessary to determine the nature and impact of the non-complying discharge.

#### 7. Records Retention

All records and information resulting from the monitoring activities required by this permit including all records of analyses performed, calibration and maintenance of instrumentation, and recordings from continuous monitoring instrumentation shall be retained for a minimum of three (3) years, and shall be submitted to Department representatives upon request. This period shall be extended during the course of unresolved litigation regarding the discharge of pollutants or when requested by the Secretary.

## 8. Solids Management

Collected screenings, sludges, and other solids removed in the course of treatment and control of wastewaters shall be stored, treated and disposed of in accord with 10 V.S.A., Chapter 159 and with the terms and conditions of any certification, interim or final, transitional operation authorization or order issued pursuant to 10 V.S.A., Chapter 159 that is in effect on the effective date of this permit or is issued during the term of this permit.

# 9. Emergency Pollution Permits

Maintenance activities, or emergencies resulting from equipment failure or malfunction, including power outages, which result in an effluent which exceeds the effluent limitations specified herein, shall be considered a violation of the conditions of this permit, unless the permittee immediately applies for, and obtains, an emergency pollution permit under the provisions of 10 V.S.A., Chapter 47, Section 1268. The permittee shall notify the Department of the emergency situation by the next working day.

10 V.S.A., Chapter 47, Section 1268 reads as follows:

"When a discharge permit holder finds that pollution abatement facilities require repairs, replacement or other corrective action in order for them to continue to meet standards specified in the permit, he may apply in the manner specified by the secretary for an emergency pollution permit for a term sufficient to effect repairs, replacements or other corrective action. The permit may be issued without prior public notice if the nature of the emergency will not provide sufficient time to give notice; provided that the secretary shall give public notice as soon as possible but in any event no later than five days after the effective date of the emergency pollution permit. No emergency pollution permit shall be issued unless the applicant certifies and the secretary finds that:

- (1) there is no present, reasonable alternative means of disposing of the waste other than by discharging it into the waters of the state during the limited period of time of the emergency;
- (2) the denial of an emergency pollution permit would work an extreme hardship upon the applicant;
- (3) the granting of an emergency pollution permit will result in some public benefit;
- (4) the discharge will not be unreasonably harmful to the quality of the receiving waters;
- (5) the cause or reason for the emergency is not due to wilful or intended acts or omissions of the applicant."

Application shall be made to the Secretary of the Agency of Natural Resources, Department of Environmental Conservation, 103 South Main Street, Waterbury, Vermont 05671-0405.

#### 10. Power Failure

In order to maintain compliance with the effluent limitations and prohibitions of this permit, the permittee shall either:

- a. Provide an alternative power source sufficient to operate the wastewater control facilities, or if such alternative power source is not in existence,
- b. Halt, reduce, or otherwise control production and/or all discharges upon the reduction, loss, or failure of the primary source of power to the wastewater control facilities.

Permit No. 3-1239 Page 10 of 14

#### B. RESPONSIBILITIES

## 1. Right of Entry

The permittee shall allow the Secretary or authorized representative, upon the presentation of proper credentials:

- to enter upon the permittee's premises in which an effluent source or any records required to be kept under terms and conditions of the permit are located;
- b. to have access to and copy any records required to be kept under the terms and conditions of the permit;
- c. to inspect any monitoring equipment or method required in the permit; or
- d, to sample any discharge of pollutants.

## 2. Transfer of Ownership or Control

This permit is not transferable without prior written approval of the Secretary. All application and operating fees must be paid in full prior to transfer of this permit. In the event of any change in control or ownership of facilities from which the authorized discharges emanate, the permittee shall provide a copy of this permit to the succeeding owner or controller and shall send written notification of the change in ownership or control to the Secretary. The permittee shall also inform the prospective owner or operator of their responsibility to make an application for transfer of this permit.

This request for transfer application must include at a minimum:

- a. a properly completed application form as provided by the Secretary and the applicable processing fee.
- b. A written statement from the prospective owner or operator certifying:
  - i. The conditions of the operation that contribute to, or affect, the discharge will not be materially different under the new ownership.
  - ii. The prospective owner or operator has read and is familiar with the terms of the permit and agrees to comply with all terms and conditions of the permit.
  - iii. The prospective owner or operator has adequate funding to operate and maintain the treatment system and remain in compliance with the terms and conditions of the permit.
- The date of the sale or transfer.

The Secretary may require additional information dependent upon the current status of the facility operation, maintenance, and permit compliance.

## 3. Confidentiality

Pursuant to 10 V.S.A. 1259(b):

"Any records, reports or information obtained under this permit program shall be available to the public for inspection and copying. However, upon a showing satisfactory to the secretary that any records, reports or information or part thereof, other than effluent data, would, if made public, divulge methods or processes entitled to protection as trade secrets, the secretary shall treat and protect those records, reports or information as confidential. Any records, reports or information accorded confidential treatment will be disclosed to authorized representatives of the state and the United States when relevant to any proceedings under this chapter."

## 4. Permit Modification

After notice and opportunity for a hearing, this permit may be modified, suspended, or revoked in whole or in part during its term for cause including, but not limited to, the following:

- a. violation of any terms or conditions of this permit;
- b. obtaining this permit by misrepresentation or failure to disclose fully all relevant facts; or
- c. a change in any condition that requires either a temporary or permanent reduction or elimination of the permitted discharge.

## 5. Toxic Effluent Standards

That if a toxic effluent standard or prohibition (including any schedule of compliance specified in such effluent standard or prohibition) is established under section 307(a) of the Federal Act for a toxic pollutant which is present in the permittee's discharge and such standard or prohibition is more stringent than any limitation upon such pollutant in the permit, the secretary shall revise or modify the permit in accordance with the toxic effluent standard or prohibition and so notify the permittee.

# 6. Oil and Hazardous Substance Liability

Nothing in this permit shall be construed to preclude the institution of legal action or relieve the permittee from any responsibilities, liabilities, or penalties to which the permittee is or may be subject under 10 V.S.A. §1281.

# 7. Civil and Criminal Liability

Except as provided in, "Bypass" (Part II, paragraph A.5.), "Power Failure" (Part II, paragraph A.10.), and "Emergency Pollution Permits" (Part II, paragraph A.9.), nothing in this permit shall be construed to relieve the permittee from civil or criminal penalties for noncompliance. Civil penalties, as authorized under 10 V.S.A. §1274 and 10 V.S.A. §8010, shall not exceed \$10,000 a day for each day of violation. Criminal

Permit No. 3-1239 Page 12 of 14

penalties, as authorized under 10 V.S.A. §1275, shall not exceed \$25,000 for each day of violation, imprisonment for up to six months, or both.

#### 8. State Laws

Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities, or penalties established pursuant to any applicable State law or regulation under authority preserved by Section 510 of the Clean Water Act.

## 9. Property Rights

Issuance of this permit does not convey any property rights in either real or personal property, or any exclusive privileges, nor does it authorize any injury to private property or any invasion of personal rights, nor any infringement of Federal, State, or local laws or regulations.

## 10. Severability

The provisions of this permit are severable, and if any provision of this permit, or the application of any provision of this permit to any circumstance, is held invalid, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected thereby.

# 11. Authority

This permit is issued under authority of 10 V.S.A. §1259 which states that: "No person shall discharge any waste, substance, or material into waters of the State, nor shall any person discharge any waste, substance, or material into an injection well or discharge into a publicly owned treatment works any waste which interferes with, passes through without treatment, or is otherwise incompatible with those works or would have a substantial adverse effect on those works or on water quality, without first obtaining a permit for that discharge from the Secretary", and under the authority of Section 402 of the Clean Water Act, as amended.

#### **PART III**

## A. OTHER REQUIREMENTS

This permit shall be modified, suspended or revoked to comply with any applicable effluent standard or limitation issued or approved under Sections 301(b) (2) (C), and (D), 304(b) (2), and 307 (a) (2) of the Clean Water Act, if the effluent standard or limitation so issued or approved:

- 1. Contains different conditions or is otherwise more stringent than any effluent limitation in the permit; or
- 2. Controls any pollutant not limited in the permit.

Permit No. 3-1239 Page 13 of 14

The permit as modified under this paragraph shall also contain any other requirements of the Vermont Water Pollution Control Act then applicable.

## B. **DEFINITIONS**

For purposes of this permit, the following definitions shall apply.

The Act - The Vermont Water Pollution Control Act, 10 V.S.A. Chapter 47

Annual Average - The highest allowable average of daily discharges calculated as the sum of all daily discharges (mg/l, lbs or gallons) measured during a calendar year divided by the number of daily discharges measured during that year.

**Average** - The arithmetic means of values taken at the frequency required for each parameter over the specified period.

The Clean Water Act - The federal Clean Water Act, as amended.

Composite Sample - A sample consisting of a minimum of one grab sample per hour collected during a 24-hour period (or lesser period as specified in the section on Monitoring and Reporting) and combined proportionally to flow over that same time period.

**Daily Discharge** - The discharge of a pollutant measured during a calendar day or any 24-hour period that reasonably represents the calendar day for purposes of sampling.

For pollutants with limitation expressed in pounds the daily discharge is calculated as the total pounds of pollutants discharged over the day.

For pollutants with limitations expressed in mg/l the daily discharge is calculated as the average measurement of the pollutant over the day.

**Grab Sample** - An individual sample collected in a period of less than 15 minutes.

**Incompatible Substance (Pollutant)** - Any waste being discharged into the treatment works which interferes with, passes through without treatment, or is otherwise incompatible with said works or would have a substantial adverse effect on these works or on water quality. This includes all pollutants required to be regulated under the Federal Clean Water Act.

Instantaneous Maximum - A value not to be exceeded in any grab sample.

Major Contributing Industry - One that: (1) has a flow of 50,000 gallons or more per average work day; (2) has a flow greater than five percent of the flow carried by the municipal system receiving the waste; (3) has in its wastes a toxic pollutant in toxic amounts as defined in standards issued under Section 307(a) of the Act; or (4) has a significant impact, either singly or in combination with other contributing industries, on a publicly owned treatment works or on the quality of effluent from that treatment works.

Maximum Day (maximum daily discharge limitation) - The highest allowable "daily discharge" (mg/l, lbs or gallons).

Page 14 of 14

Mean - The mean value is the arithmetic mean.

Monthly Average - (Average monthly discharge limitation) - The highest allowable average of daily discharges (mg/l, lbs or gallons) over a calendar month, calculated as the sum of all daily discharges (mg/l, lbs or gallons) measured during a calendar month divided by the number of daily discharges measured during that month.

NPDES - The National Pollutant Discharge Elimination System.

Secretary - The Secretary of the Agency of Natural Resources

State Certifying Agency Agency of Natural Resources

Department of Environmental Conservation

Wastewater Management Division

103 South Main Street

Waterbury, Vermont 05671-0405

Weekly Average - (Average weekly discharge limitation) - The highest allowable average of daily discharges (mg/l, lbs or gallons) over a calendar week, calculated as the sum of all daily discharges (mg/l, lbs or gallons) measured during a calendar week divided by the number of daily discharges measured during that week.