



Blue Flame Synthetic Blend Diesel Engine Oil

PALADIN BLUE FLAME® SAE 15W-40 synthetic blend heavy duty diesel engine oil is purpose built to be the most robust oil available for maximum engine lubrication and wear protection. It is designed to specifically address the extreme performance demands of turbo, or super-charged, diesel engines modified for higher compression for more horsepower and torque.

KEY FEATURES:

- Synthetic blend SAE 15W-40 formula
- Exceeds API service levels CJ-4, CI-4, CH-4, CG-4, CF-4 and current OEM warranty requirements for extended service
- Meets, or exceeds, pre and post-2007 emissions requirements
- Safe for use in applications equipped with Exhaust Gas Recirculation (EGR) and diesel particulate filters (DPF) systems
- Advanced viscosity and soot control technology for shear stability and engine cleanliness
- High reserve alkalinity chemistry reduces corrosive wear and oil oxidation

APPLICATIONS:

Diesel Engine Service

- Drain intervals may be extended further with oil analysis.
- 2007-2009 Caterpillar C13 and C15 on-highway engines must follow OEM-recommended drain interval.
- 2007-2010 Dodge 6.7L, Ford 6.4L and GM 6.6L LMM light-duty diesel pickups must follow OEM- recommended drain interval. Drain intervals may be extended with oil analysis.

Gasoline Engine Service

- Suitable for use in 4-stroke gasoline engines.
- Do not use in wet clutch applications

SPECIFICATIONS & APPROVALS:

API CJ-4, CI-4 Plus, CI-4, CH-4, CG-4, SM
ACEA E7-04, E6, E5-02, E4-99#2, E3 & E2
Detroit Diesel 93K218, 93K215, 93K214
Caterpillar SEBU 6385
Caterpillar ECF-3, ECF-2*, and ECF-1-a
Cummins CES 20081Ford M2C171-C & D
General Motors 9985930
Global DHD-1

JASO DH-2, DH-1, MA
Mack EO-O Premium Plus 2007
MAN 271 & 3275
Mercedes Benz p228.31
MTL 5044 (MTU Type 1 and 2)
Renault VI RLD-3
Volvo VDS-4, VDS-3, & VDS-2







Note: Extended drain intervals are not recommended when using biofuels containing >10% Ethanol or 5% biodiesel (B5). Follow OEM drain intervals or extend drain intervals with oil analysis.


CHAMPION BRANDS, L.L.C. • 1001 Golden Drive • Clinton, MO 64735
ORDER DESK 800-821-5693

SUPERIOR WEAR PROTECTION: A Closer Look

PALADIN BLUE FLAME® SAE 15W-40 synthetic blend heavy duty diesel engine oil provides exceptional wear protection as demonstrated below and succeeded in significantly exceeding API and OEM specifications including Detroit Diesel, Mack/Volvo and Cummins.



Oil Consumption Performance Across Industry Engine Tests



Paladin Blue Flame's high performance shear stability chemistry delivers lower oil volatility and consumption than any conventional diesel engine oil and is proven to exceed OEM performance targets.

TYPICAL PROPERTIES

SAE Grade	15W-40
Product Code	6358
TBN	11.0
Appearance/Color	Blue
Gravity API @ 60° F	30.4
cSt @ 40°C	113
cSt @ 100°C	15.2
Viscosity Index	140
Pour Point ° F	-30
Flash Point ° F	438
Sulfated Ash %wt	<1.0