

CP-4600 Series Lubricants

The CP-4600 Series lubricants are custom-blended polyolalphaolefin (PAO) synthetic hydrocarbon fluids.

Primary benefits include:

- Excellent low and high temperature performance
- Reduced volatility
- Chemically inert (hydrolytic stability)
- Compatible with a wide variety of seals, paints, metals, and plastics normally used in mineral oil applications

These high-performance lubricants are recommended for chemical compressor applications that are compatible with mineral oil.

For CP-4600 Series products approved for use with UOP catalysts, consult your CPI representative.

Preliminary Product Selection Guide

Product Name	Viscosity*				Viscosity Index ASTM D2270
	@ 40° C cSt ASTM D445	@ 100° C cSt	@ 100° F SUS	@ 210° F SUS	
CP-4600-32	31.4	6.00	162	46.3	140
CP-4600-46	46.9	7.90	241	52.7	139
CP-4600-68	68.5	10.4	353	61.6	140
CP-4600-100	97.3	14.2	502	76.2	150
CP-4600-150	146	19.4	756	98.2	152

* These values are not intended for use in preparing specifications. For assistance, consult your CPI representative.



REPRESENTATIVE

Rolenor USA LLC

4801 Woodway, Suite 306 · Houston, TX 77056

832-308-9332 · email: sales@rolenor.com