



# CP-4601 Series Lubricants

CP-4601 Series lubricants are custom formulated polyalphaolefin (PAO) synthetic hydrocarbon fluids providing:

- Improved lubrication at high and low temperatures
- Reduced volatility
- Superior corrosion protection
- Excellent oxidation stability



These high performance lubricants are recommended for use in:

- Flooded rotary screw compressors
- Liquid ring vacuum pumps

For CP-4601 Series lubricants approved for federally inspected food processing facilities (H2) — consult your CPI representative. Your local CPI representative can help you determine the appropriate product and viscosity for your needs.



All CPI lubricants are Kosher, Pareve, and Halal registered.

## Preliminary Product Selection Guide

Product Name	Physical Properties*				
	Viscosity @ 40° C cSt ASTM D445	Viscosity @ 100° C cSt ASTM D445	Viscosity Index ASTM D2270	Pour Point °F (°C) ASTM D97	Flash Point °F (°C) ASTM D92
CP-4601-5 Refineries	6.94	2.41	202	-100 (-73)	330 (165)
CP-4601-15 Vacuum Pumps and Industrial	17.0	3.90	125	-100 (-73)	425 (210)
CP-4601-32 Refineries	30.7	5.97	144	-90 (-68)	470 (243)
CP-4601-46 Refineries	43.3	7.45	138	-71 (-57)	515 (268)
CP-4601-68 Turbine Feed and Landfill Gas Gathering	64.4	10.2	145	-65 (-54)	515 (268)
CP-4601-100 Extreme Duty Turbine Feed and Landfill Gas Gathering	98.3	14.0	145	-55 (-48)	520 (271)
CP-4601-150 Extreme-Duty Turbine Feed and Landfill Gas Gathering	142	18.5	147	-49 (-45)	515 (268)
CP-4601-220	220	26.9	157	-44 (-42)	525 (274)
CP-4601-320	293	31.2	146	-30 (-34)	540 (282)
CP-4601-460	464	48.1	163	-27 (-33)	505 (263)

\* These values are not intended for use in preparing specifications. For assistance, consult your CPI representative.



### REPRESENTATIVE

**Rolenor USA LLC**

4801 Woodway, Suite 306 · Houston, TX 77056

832-308-9332 · email: [sales@rolenor.com](mailto:sales@rolenor.com)