

# CP-4624-F Series Lubricants

The CP-4624-F Series lubricants are custom-blended synthetic hydrocarbon fluids. Primary benefits include:

- Excellent low and high temperature performance
- Reduced volatility
- Compatible with a wide variety of seals, paints, metals, and plastics normally used in mineral oil applications
- Superior corrosion protection
- Excellent oxidation stability

These high-performance lubricants are recommended for use:

- As a sealing fluid for pumps
- As a lubricant /coolant for CO2 compressors
- For other chemical processing applications requiring improved chemical stability and compatibility with mineral oil

CP-4624-F Series products are approved for federally inspected meat and poultry plant applications with incidental food contact (H-1). Your local CPI representative can help you determine the appropriate product and viscosity for your needs.



For information regarding NSF H-1 or NSF H-2 approval, please contact your local CPI sales representative.

## Preliminary Product Selection Guide

Product Name	Viscosity*				Viscosity Index ASTM D2270
	@ 40° C cSt ASTM D445	@ 100° C cSt	@ 100° F SUS	@ 210° F SUS	
CP-4624-68-F	68.5	10.4	353	61.6	140
CP-4624-100-F	97.3	14.2	502	76.2	150
CP-4624-150-F	145	19.4	751	98.2	153
CP-4624-220-F	224	26.6	1167	131	152
CP-4624-320-F	320	33.0	1678	161	145
CP-4624-460-F	443	46.0	2319	222	161

\* These values are not intended for use in preparing specifications. For assistance, consult your CPI representative.



### REPRESENTATIVE

**Rolenor USA LLC**

4801 Woodway, Suite 306 · Houston, TX 77056

832-308-9332 · email: sales@rolenor.com