

CP-6000 Series Lubricants

The CP-6000 Series lubricants are custom-blended, chemically inert synthetic lubricants with a polyalphaolefin (PAO) base. Primary benefits include:

- Excellent shear stability
- Low-temperature stability
- Excellent low and high temperature performance
- Superior corrosion protection

These high-performance lubricants are recommended for harsh chemical environments, particularly:

- Compressors handling chemical gases such as hydrogen chloride and methyl chloride

Your local CPI representative can help you determine the appropriate product and viscosity for your needs.

Preliminary Product Selection Guide

Product Name	Viscosity*				Viscosity Index ASTM D2270
	@ 40° C cSt ASTM D445	@ 100° C cSt	@ 100° F SUS	@ 210° F SUS	
CP-6000-5	5.10	1.70	44.0	31.9	122
CP-6000-15	16.8	3.80	90.8	39.1	117
CP-6000-32	31.4	6.00	162	46.3	140
CP-6000-46	46.9	7.90	241	52.7	139
CP-6000-68	68.5	10.4	353	61.6	139

* These values are not intended for use in preparing specifications. For assistance, consult your CPI representative.



REPRESENTATIVE

Rolenor USA LLC

4801 Woodway, Suite 306 · Houston, TX 77056

832-308-9332 · email: sales@rolenor.com