



MARSHALL'S COVE BRAND MARINE PAINT

TRADITIONAL DURABLE MARINE FINISH



MATERIAL SAFETY DATA SHEET FOR COATINGS AND RELATED MATERIALS

SECTION I MANUFACTURER IDENTIFICATION

Manufacturer:	Marshall's Cove Brand Marine Paint (MCBMP)	Product Information (MCBMP):	425.260.3509
Address:	P.O. Box 836 Bellevue, Washington 98009	Hazard Rating:	This Product:
Product Name:	Marshall's Cove Marine Enamel	0 Lowest	Health 2
Product Class:	Pigmented, Alkyd Resin Solution	1	Flammability 1
Prepared:	January 2011	2	Reactivity 0
		3	Personal
		4 Extreme	Protection G

SECTION II HAZARDOUS INGREDIENTS

Ingredient:	CAS Number:	Percent (By Weight):	Occupational TLV (ACGIH):	Exposure PEL (OSHA):
Mineral Spirits	8052-41-3	39%	100ppm	100ppm

Pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372, this product contains or may contain a toxic chemical in a quantity subject to the reporting requirements under Section 313.

SECTION III PHYSICAL DATA

Boiling Range:	307° to 389° F	% Organic Volatile By Volume:	55%
Weight/Gallon:	9.5 lbs	Solubility In Water:	Nil
Vapor Pressure:	2.6 mmhg @ 20° C	VOC:	437 Grams/Liter (Less Water)
Vapor Density:	Heavier Than Air: <input checked="" type="checkbox"/> Lighter Than Air: <input type="checkbox"/>	Reactivity In Water:	Nil
Evaporation Rate:	Faster Than Ether: <input type="checkbox"/> Slower Than Ether: <input checked="" type="checkbox"/>	Appearance:	Oily liquid, color of tint

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flammability Classification:	OSHA: Combustible Flash Point: 107° F	Class: 3 LEL: 0.7%	DOT: Combustible UN Number: 1263
Extinguishing Media:	Foam, CO2, Dry Chemical, or Water Fog Use the above or any Class B extinguishing agent. Water may be unsuitable as an extinguishing medium, but helpful in keeping adjacent containers cool.		
Special Firefighting Procedures:	Firefighters and others exposed to vapors or products of combustion should wear self-contained breathing apparatus. Evacuate area of unprotected personnel. Wear protective clothing.		
Unusual Fire and Explosion Hazards:	Vapors may form an explosive mixture in air and may be ignited by sparks, pilot lights, etc. Closed containers may rupture when exposed to extreme heat.		

SECTION V HEALTH HAZARD DATA

Effects of Overexposure:	Skin: This material may cause irritation, sensitization, or defatting of skin upon prolonged or repeated contact.
	Inhalation: Excessive exposure to vapors or spray mist can result in headache, dizziness, nausea and loss of consciousness. Some reports have associated repeated & prolonged occupational overexposure to solvents with permanent brain & nervous system damage.
	Eyes: This material may be an eye irritant.
Medical Conditions Prone to Aggravation by Exposure:	None, when used in accordance with safe handling instructions. (See Section VIII)
Emergency and First Aid Procedures:	Skin: Promptly wash with soap and water. Remove and wash any contaminated clothing before reuse.
	Eyes: Flush with large quantities of water for 15 minutes and seek medical attention.
	Swallowing: If ingested do not induce vomiting; keep person warm and quiet and get medical attention. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal.
	Inhalation: Remove victim to fresh air immediately. If respiratory symptoms develop, seek medical attention at once.
Primary Route(s) of Entry:	Inhalation, Dermal, Ingestion
Carcinogenicity:	This product contains no known carcinogens in reportable quantities as defined by ACGIH, OSHA, NTP, IARC.

SECTION VI  **REACTIVITY DATA**

Stability: Stable: Unstable: | **Hazardous Polymerization:** May Occur: Will Not Occur:

Hazardous Decomposition Products: Incomplete combustion can yield carbon monoxide and toxic vapors.

Conditions to Avoid: Heat, sparks & open flame. If product contains aluminum, moisture in closed containers will generate hydrogen gas.

Incompatibility: Avoid contact with strong oxidants, acids, bases and epoxy hardeners under uncontrolled conditions.

SECTION VII  **SPILL OR LEAK PROCEDURES**

Steps to be Taken in Case Material is Released or Spilled: Remove all sources of ignition. Ventilate area. Absorb spill with an absorbent material such as sawdust, vermiculite or sand and place material into a closed container. If large spill, dike area to prevent this material from entering water systems or sewers. Wear protective equipment during cleanup.

Waste Disposal Method: Dispose in accordance with Local, State and Federal agencies. Ground handling equipment to prevent sparks.

For Further Information: Contact your State or Local Waste Agency or the United States Environmental Protection Agency's RCRA Hotline at 1-800-424-9346 or 1-202-382-3000.

SECTION VIII  **SAFE HANDLING AND USE INFORMATION**

KEEP OUT OF THE REACH OF CHILDREN.

Respiratory Protection: A canister-type respirator must be worn to prevent the inhalation of vapors or spray mist when the TLV or PEL is exceeded.

Ventilation: General ventilation is required during normal use. Local ventilation may be required during certain operations to keep exposure level below the limits listed in Section II of this data sheet.

Protective Gloves: Chemical resistant nitrile, neoprene or rubber gloves required.

Eye Protection: Wear face shield or chemical goggles.

Other Protective Equipment: Wear protective clothing to prevent skin contact. Eye wash station and safety shower should be available.

Hygienic Practices: Wash hands before eating or smoking.

SECTION IX  **SPECIAL PRECAUTIONS**

Precautions to be Taken in Handling and Storing: Avoid prolonged or repeated inhalation of heated vapors or spray mist. Keep away from heat or open flame. This material may cause sensitization. Do not get in eyes, on skin or clothing. Do not allow contaminated clothing to contact skin. Do not weld on full or empty containers. Keep containers closed when not in use, and properly labeled.

SECTION X  **SUPPLEMENTAL INFORMATION**

This material has been categorized as having the following hazard(s) as defined by SARA Title III regulations (40 CFR 370): **ACUTE, FIRE**

The information in this data sheet is believed to be accurate and true at the time of preparation of this document. This is not a warranty of product or product specification. The end-user of this product is advised to verify in advance that the information in this sheet is current, applicable, and suitable to their circumstances.

 **MARSHALL'S COVE BRAND MARINE PAINT** 

PETERMARSHALL, PROPRIETOR | 425.260.3509 | PETER@MARSHALLSCOVEMARINEPAINT.COM | WWW.MARSHALLSCOVEMARINEPAINT.COM | PO BOX 836 | BELLEVUE, WA 98009