

02 Recessed Spots Fixed LED>The IP65 Bathroom Range

10106V/W/W



6W Recesed Spot fixed LED, IP65.

Complete with 500mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



Gallery



Physical Specification

Item Group	02 Recessed Spots Fixed LED
Family	The IP65 Bathroom Range
Order Code	10106V/W/W
Colour	White
Material	Die Cast + Glass
Shape	Circular
Height	81mm

Diameter	110mm
Cutout Hole Diameter	94mm
Recessed Ceiling	Yes
Depth Required	100mm
Indoor	Yes
Outdoor	Yes
Adjustable	No
IK Rating	8
Gear	Built In
Gear	Built In
Fitting + Driver	400.0401/
Input Voltage	100-240V
50 Hz 60 Hz	Yes Yes
Safety Class	
Power(Watts)	6W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	


Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
IP Rating	IP65
Light Source	LED built in
LED Type	СОВ
LED Brand	Cree

Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	3-6W
Power Factor	0,5
Constant Current	Yes
500mA	6-12V
IP Rating	IP20
Safety Class	
Dimmable	No
	Plastic
Housing Material	i lastic
Housing Material Brand	Eaglerise
Brand	
Brand	
Brand Ulumination Data	Eaglerise
Brand Ilumination Data Colour Temperature	Eaglerise 3000K
Brand Lumination Data Colour Temperature Lumen Output	Eaglerise 3000K 460lm
Brand Lumination Data Colour Temperature Lumen Output Light Efficiency	3000K 460Im 76,67Im/W
Brand Colour Temperature Lumen Output Light Efficiency CRI	3000K 460lm 76,67lm/W
Brand Lumination Data Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3000K 460lm 76,67lm/W
Brand Lumination Data Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3000K 460lm 76,67lm/W
Brand Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3000K 460lm 76,67lm/W 80 25°
Ilumination Data Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Pcs/Carton	Eaglerise 3000K 460lm 76,67lm/W 80 25° ☐
Brand Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3000K 460lm 76,67lm/W 80 25°
Ilumination Data Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Pcs/Carton	Eaglerise 3000K 460lm 76,67lm/W 80 25° ☐

1

LED Number

Energy Label



Certification & Warranty	
Warranty	3 Years
Weee Directive	Yes