



30W LED recessed downlight, IP20. Ideal for general lighting applications.

Complete with 750mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Physical Specification

Item Group

06 Downlights Fixed LED

Family

The COB Downlight Range Die Cast

Order Code

10130CA/W/C

Colour

White

Material

Die Cast

Shape



Circular


Height

110mm

| | |
|----------------------|-------|
| Diameter | 230mm |
| Cutout Hole Diameter | 210mm |
| Recessed Ceiling | Yes |
| Depth Required | 140mm |
| Indoor | Yes |
| Adjustable | No |

Electrical Characteristics

| Gear | External-Included |
|------------------|---------------------------------------------------------------------------------------|
| Fitting + Driver | |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class |  |
| Power(Watts) | 30W |
| IP Rating | IP20 |
| Light Source | LED built in |
| Dimmable | No |
| F Mark |  |

| Fitting | |
|---------------|---------------------------------------------------------------------------------------|
| Input Type | Constant Current |
| Input Current | 750mA |
| Voltage | 38V |
| Safety Class |  |
| Power(Watts) | 28,5W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | COB |
| LED Brand | Epistar |

Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

19-31,5W

Power Factor

0,9

Constant Current

Yes

750mA

25-42V

IP Rating

IP20

Safety Class



Dimmable

No

Ambient Temp

45°C

Operating Temp

85°C

Housing Material

Plastic

Output Terminal

Cable

Brand

Lifud

Protection

Short Circuit and Overload

Illumination Data

Colour Temperature

4000K

Lumen Output

2700lm

Light Efficiency

90lm/W

CRI

80

Beam Angle

60°

Illumination Diagram



Packing Info

| | |
|------------|---------------|
| Box Length | 23,5cm |
| Box Width | 11,5cm |
| Box Height | 23,5cm |
| Box Weight | 1,4Kg |
| Pcs/Carton | 10 |
| Barcode | 5291889052043 |
| HS Code | 9405409900 |

Energy Label



Certification & Warranty

| | |
|------------------|----------|
| Warranty | 2 Years |
| Average Lifetime | 30000hrs |
| Weee Directive | Yes |