



7W COB LED recessed adjustable spot, for general lighting applications.

Requires 700mA constant current LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Must be ordered separately



89015A

Related items



89015AT

Physical Specification

Item Group	04 Recessed Spots Adjustable LED
Family	The COB Recessed Cylinders
Order Code	11107C/W/W
Colour	White
Material	Die Cast
Shape	Circular
Height	85mm
Diameter	90mm
Cutout Hole Diameter	83mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Adjustable	2 Directions

Electrical Characteristics

Fitting

Input Type	Constant Current
Input Current	700mA
Voltage	10V
Safety Class	III
Power(Watts)	7W
IP Rating	IP20
Light Source	LED built in

LED Type
LED Brand
LED Number
Cable Length
F Mark

COB
Bridgelux
1
40cm


Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Beam Angle
Illumination Diagram
Dark Light

3000K
550lm
78,57lm/W
90
36°

Yes

Packing Info

Box Length
Box Width
Box Height
Pcs/Carton
Barcode
HS Code

10cm
10cm
10cm
36
5291889049241
9405409900

Certification & Warranty

Warranty

5 Years

Weee Directive

Yes
