

04 Recessed Spots Adjustable LED>The Compact Spots

11109KD/W/W



9,2W LED adjustable recessed spot, with built-in 230V LED driver, made of plastic. Supplied with TRIAC dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.













Downloads









Dimensions



Gallery




Physical Specification

04 Recessed Spots Adjustable LED
The Compact Spots
11109KD/W/W
Aluminium
Acrylic
Circular
62mm

Diameter	86mm
Cutout Hole Diameter	67mm
Recessed Ceiling	Yes
Depth Required	90mm
Indoor	Yes
Adjustable	1 Direction
ectrical Characteristics	
_	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	9,2W
IP Rating	IP20
Light Source	LED built in
Dimmable	Yes
Dimmer type	Triac
F Mark	F
Fitting	
Input Type	Constant Current
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Sanan
LED Number	1
F Mark	F

Colour Temperature Lumen Output 620Im Light Efficiency 67,4Im/W CRI Beam Angle 38° Illumination Diagram	Gear	
FOUND Power (Watts) Pow	Gear Type	Led Driver
Form Power (Watts) Powe	Input Voltage	220-240V
Power(Watts) 9,2W Constant Current Yes IP Rating IP20 Safety Class □ Dimmable Yes Output Terminal Cable Colour Temperature Lumen Output 620Im Light Efficiency 67,4Im/W CRI 80 Beam Angle 38° Illumination Diagram Illumination Diagram Pesking Info 10cm Box Weight 0,150Kg Pos/Carton 48 Barcode 5291889038689	50 Hz	Yes
Constant Current Yes IP Rating IP20 Safety Class □ Dimmable Yes Output Terminal Cable Illumination Data Colour Temperature 3000K Lumen Output 620lm Light Efficiency 67,4lm/W CRI 80 Beam Angle 38° Illumination Diagram □ Packing Info □ Box Length 10cm Box Width 10cm Box Weight 9,150Kg Pos/Carton 48 Barcode 529188903888	60 Hz	Yes
IP Rating	Power(Watts)	9,2W
Dimmable	Constant Current	Yes
Dimmable Yes	IP Rating	IP20
Output Terminal Cable Illumination Data 3000K Colour Temperature 3000K Lumen Output 620lm Light Efficiency 67,4lm/W CRI 80 Beam Angle 38° Illumination Diagram 38° Packing Info 10cm Box Weight 10cm Box Weight 8,5cm Box Weight 0,150Kg Pes/Carton 48 Barcode 5291889038689	Safety Class	
Colour Temperature	Dimmable	Yes
Colour Temperature 3000K Lumen Output 620Im Light Efficiency 67,4Im/W CRI 80 Beam Angle 38° Illumination Diagram Illumination Diagram Packing Info 10cm Box Length 10cm Box Width 10cm Box Height 8,5cm Box Weight 0,150Kg Pcs/Carton 48 Barcode 5291889038689	Output Terminal	Cable
Colour Temperature 3000K Lumen Output 620Im Light Efficiency 67,4Im/W CRI 80 Beam Angle 38° Illumination Diagram Illumination Diagram Packing Info 10cm Box Length 10cm Box Width 10cm Box Height 8,5cm Box Weight 0,150Kg Pcs/Carton 48 Barcode 5291889038689		
Lumen Output 620lm Light Efficiency 67,4lm/W CRI 80 Beam Angle 38° Illumination Diagram Illumination Diagram Packing Info 10cm Box Length 10cm Box Width 10cm Box Height 8,5cm Box Weight 0,150Kg Pes/Carton 48 Barcode 5291889038689	Illumination Data	
Lumen Output 620lm Light Efficiency 67,4lm/W CRI 80 Beam Angle 38° Illumination Diagram Illumination Diagram Packing Info 10cm Box Length 10cm Box Width 10cm Box Height 8,5cm Box Weight 0,150Kg Pes/Carton 48 Barcode 5291889038689	Colour Temperature	200014
Light Efficiency 67,4lm/W CRI 80 Beam Angle 38° Illumination Diagram □ Packing Info 10cm Box Length 10cm Box Width 10cm Box Height 8,5cm Box Weight 0,150Kg Pcs/Carton 48 Barcode 5291889038689		
CRI 80 Beam Angle 38° Illumination Diagram Illumination Diagram Packing Info 10cm Box Length 10cm Box Width 10cm Box Height 8,5cm Box Weight 0,150Kg Pcs/Carton 48 Barcode 5291889038689		
Beam Angle 38° Illumination Diagram Illumination Diagram Packing Info 10cm Box Length 10cm Box Width 10cm Box Height 8,5cm Box Weight 0,150Kg Pcs/Carton 48 Barcode 5291889038689		
Illumination Diagram		
Packing Info		
Box Length 10cm Box Width 10cm Box Height 8,5cm Box Weight 0,150Kg Pcs/Carton 48 Barcode 5291889038689	Illumination Diagram	
Box Length 10cm Box Width 10cm Box Height 8,5cm Box Weight 0,150Kg Pcs/Carton 48 Barcode 5291889038689		
Box Width 10cm Box Height 8,5cm Box Weight 0,150Kg Pcs/Carton 48 Barcode 5291889038689	Packing Info	
Box Height 8,5cm Box Weight 0,150Kg Pcs/Carton 48 Barcode 5291889038689	Box Length	10cm
Box Weight 0,150Kg Pcs/Carton 48 Barcode 5291889038689	Box Width	10cm
Pcs/Carton 48 Barcode 5291889038689	Box Height	8,5cm
Barcode 5291889038689	Box Weight	0,150Kg
	Pcs/Carton	48
HS Code 9405409900	Barcode	5291889038689
	HS Code	9405409900



Certification & Warranty	
Warranty	2 Years
Weee Directive	Yes