



4,5W COB LED cement with black reflector, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery





Physical Specification

Item Group	14 Wall & Ceiling LED
Family	The COB Indoor Round Cylinders
Order Code	12104M/W
Colour	White
Material	Cement
Shape	Circular
Height	110mm

Diameter	75mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No


Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	4,5W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	350mA
Voltage	8,6V
Power(Watts)	3W
IP Rating	IP20
Light Source	LED built in
LED Brand	Bridgelux

Gear	
Gear Type	Led Driver
Input Voltage	100-240V

50 Hz
60 Hz
Power(Watts)
Power Factor
Constant Current
350mA
IP Rating
Safety Class
Dimmable
Brand

Yes
Yes
2,1-4,2W
0,95
Yes
6-12V
IP20

No
Eaglerise

Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Beam Angle
Illumination Diagram
Dark Light

3000K
350lm
77,78lm/W
90
40°

Yes

Packing Info

Box Length
Box Width
Box Height
Pcs/Carton
Barcode
HS Code

13cm
13cm
16,5cm
18
5291889056096
9405409900

Energy Label



Certification & Warranty

Warranty

2 Years

Weee Directive

Yes