

14 Wall & Ceiling LED>The SMD Cylinders Aluminium

12125L/W/W



25W COB LED ceiling downlight, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Physical Specification

Item Group	14 Wall & Ceiling LED
Family	The SMD Cylinders Aluminium
Order Code	12125L/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	115mm
Diameter	162mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	25W
IP Rating	IP40
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	600mA
Input Current Voltage	600mA 40V
Voltage	40V
Voltage Power(Watts)	40V 24W
Voltage Power(Watts) IP Rating	40V 24W IP20
Voltage Power(Watts) IP Rating Light Source	40V 24W IP20 LED built in
Voltage Power(Watts) IP Rating Light Source LED Type	40V 24W IP20 LED built in SMD 5630
Voltage Power(Watts) IP Rating Light Source LED Type LED Brand LED Number	40V 24W IP20 LED built in SMD 5630 Samsung
Voltage Power(Watts) IP Rating Light Source LED Type LED Brand	40V 24W IP20 LED built in SMD 5630 Samsung
Voltage Power(Watts) IP Rating Light Source LED Type LED Brand LED Number	40V 24W IP20 LED built in SMD 5630 Samsung
Voltage Power(Watts) IP Rating Light Source LED Type LED Brand LED Number	40V 24W IP20 LED built in SMD 5630 Samsung 48
Voltage Power(Watts) IP Rating Light Source LED Type LED Brand LED Number Gear Gear Type	40V 24W IP20 LED built in SMD 5630 Samsung 48
Voltage Power(Watts) IP Rating Light Source LED Type LED Brand LED Number Gear Gear Type Input Voltage	40V 24W IP20 LED built in SMD 5630 Samsung 48 Led Driver 220-240V

Power Factor	0,9
Constant Current	Yes
600mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Illumination Data	
Colour Temperature	3000K
Lumen Output	2050lm
Light Efficiency	82Im/W
CRI	80
Beam Angle	90°
Illumination Diagram	
Packing Info	
Box Length	17,5cm
Box Width	17,5cm
Box Height	12,5cm
Box Weight	0,83Kg
Pcs/Carton	36
Barcode	5291889041009
HS Code	9405409900

Energy Label



Weee Directive

Certification & Warranty	
Warranty	2 Years

Yes