



50W UGR19 Linear system with diffuser for surface or suspended installation, ideal for offices.

Complete with 1500mA driver.

Complies with standard EN60598-1 and any other specific standards.



### Downloads



### Dimensions



### Gallery



### Accessories



050170



050170C/B

Related items



38150E/B

Physical Specification

Item Group	New 2021 Edition 3
Family	Office & Kitchen
Order Code	38151A/B/W
Colour	Black
Material	Aluminium
Shape	Rectangular
Length	1500mm
Width	70mm
Height	35mm
Surface Ceiling	Yes
Suspended Ceiling	Yes
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	50W
IP Rating	IP20

Light Source	LED built in
Dimmable	No
Cable Length	300cm
F Mark	

#### Fitting

Input Type	Constant Current
Input Current	1500mA
Voltage	31V
Power(Watts)	46,5W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar

#### Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	45-63W
Power Factor	0,9
Constant Current	Yes
1500mA	30-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Brand	AGT
Protection	0

#### Illumination Data

Colour Temperature	3000K
Lumen Output	4250lm
Light Efficiency	85lm/W
CRI	90
Beam Angle	120°
Illumination Diagram	
UGR	19

#### Packing Info

Pcs/Carton	9
Barcode	5291889070252
HS Code	9405409900

#### Certification & Warranty

Warranty	3 Years
Weee Directive	Yes