



8W corner for 38152R.

Complete with 250mA driver , 4pcs fixing clips, 4pcs connectors & 2pcs end cups.


Complies with standard EN60598-1 and any other specific standards.



### Downloads



### Dimensions



### Gallery



### Physical Specification

Item Group

12 Office & Kitchen

Family

Recessed LED Linear Profiles

Order Code

38152RC/W/C

Colour

White

Material

Aluminium

Diffuser Material

Plastic

Shape

Rectangular

Length	164x164mm
Width	70mm
Height	60mm
Cutout Hole Width	160x160mm
Cutout Hole Length	60mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Adjustable	No

## Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	8W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	250mA
Voltage	30V
Power(Watts)	7,5W
IP Rating	IP20
Light Source	LED built in

LED Type	SMD 2835
LED Brand	Epistar
LED Number	60

## Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	7,5-10,5W
Power Factor	0,9
Constant Current	Yes
250mA	30-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Metal
Output Terminal	Connector
Brand	ATG

## Illumination Data

Colour Temperature	4000K
Lumen Output	720m
Light Efficiency	90lm/W
CRI	90
Illumination Diagram	

## Packing Info

Pcs/Carton	10
Barcode	5291889062660

HS Code

9405409900

Certification & Warranty

Warranty

3 Years

Weee Directive

Yes