



IP65 LED fitting to replace T8 IP65 traditional waterproof fluorescent. Stainless steel clips included. Polycarbonate body and diffuser.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



## Downloads



## Dimensions



## Gallery



## Physical Specification

Item Group

21 Industrial & Floodlights

Family

The High Power IP65 LED Range Single

Order Code

38158M/C

Colour

Grey

Material

PC

Diffuser Material

PC

Shape

Rectangular

Length	1515mm
Width	84mm
Height	80mm
Surface Ceiling	Yes
Surface Wall	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No
IK Rating	8

### Electrical Characteristics

Gear	Built In
<b>Fitting + Driver</b>	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	
<b>Fitting</b>	
Input Type	Constant Current
Input Current	700mA
Voltage	54V
Power(Watts)	37,8W
IP Rating	IP65
Light Source	LED built in

LED Type

SMD 2835

LED Brand

Everlight

Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

14-42W

Power Factor

0,9

Constant Current

Yes

700mA

20-54V

IP Rating

IP20

Safety Class



Dimmable

No

Housing Material

Plastic

Output Terminal

Connector

Brand

Tridonic

## Illumination Data

Colour Temperature

4000K

Lumen Output

3200lm

Light Efficiency

80lm/W

CRI

80



Illumination Diagram

## Packing Info

Box Length

152cm

Box Width

8,3cm

Box Height

9cm

Box Weight

1,6Kg

Pcs/Carton

9

Barcode

5291889055013

HS Code

9405104090

## Certification & Warranty

Warranty

3 Years

Weee Directive

Yes