




120x30 recessed LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications.

Requires 1200mA LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Must be ordered separately



89048

Accessories



050017



050108

Related items



89048T



89050L



89050TLD

Physical Specification

Item Group	06 Downlights Fixed LED
Family	The Rectangular Panels Aluminium
Order Code	50148RE/W/D
Colour	White
Material	Aluminium
Diffuser Material	Acrylic
Shape	Rectangular
Length	1195mm
Width	295mm
Height	20mm
Recessed T-Ceiling	Yes
Depth Required	50mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Fitting	
Input Type	Constant Current
Input Current	1200mA
Voltage	38V
Safety Class	III
Power(Watts)	48W
IP Rating	IP20

Light Source
LED Type
LED Brand
LED Number

LED built in
SMD 2835
Epistar
240

Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Beam Angle
Illumination Diagram


6000K
4100lm
85,41lm/W
80
120°


Packing Info

Pcs/Carton
Barcode
HS Code

4
5291889041986
9405109890

Energy Label



Certification & Warranty

Warranty	2 Years
Average Lifetime	30000 hours
Weee Directive	Yes