

## 08 Downlights Adjustable LED>The COB Box Type Shop Range

# 51120/W/W



20W COB LED Recessed adjustable downlight, COB square range, IP20.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



#### Downloads









#### Dimensions



#### Gallery



#### **Physical Specification**


Item Group	08 Downlights Adjustable LED
Family	The COB Box Type Shop Range
Order Code	51120/W/W
Colour	White
Material	Aluminium
Shape	Rectangular
Length	190mm

Width	190mm
Height	100mm
Cutout Hole Width	165mm
Cutout Hole Length	165mm
Recessed Ceiling	Yes
Depth Required	140mm
Indoor	Yes
Adjustable	2 Directions
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	37,3V
Safety Class	<u> </u>
Power(Watts)	18,65W
IP Rating	IP20
Light Source	LED built in

LED Type	СОВ
LED Brand	Sanan
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	13,5-21W
Power Factor	0,9
Constant Current	Yes
500mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Housing Material	Plastic
Housing Material  Illumination Data	Plastic
Illumination Data	
Illumination Data  Colour Temperature	3000K
Illumination Data  Colour Temperature  Lumen Output	3000K 1400lm
Colour Temperature  Lumen Output  Light Efficiency	3000K 1400lm 70lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	3000K 1400lm 70lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	3000K 1400lm 70lm/W
Illumination Data  Colour Temperature  Lumen Output  Light Efficiency  CRI	3000K 1400lm 70lm/W 80 36°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	3000K 1400lm 70lm/W 80 36°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	3000K 1400lm 70lm/W 80 36°
Illumination Data  Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	3000K 1400lm 70lm/W 80 36°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	3000K 1400lm 70lm/W 80 36°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length	3000K 1400lm 70lm/W 80 36°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width	3000K 1400lm 70lm/W 80 36°  23cm

Pcs/Carton	12
Barcode	5291889041122
HS Code	9405409900

# Energy Label



## Certification & Warranty

Warranty	2 Years
Weee Directive	Yes