elights

40W COB LED Recessed adjustable downlight, COB square range, IP20.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.

IP20 80 CRI ADJUSTABLE CE

Downloads

IES

Dimensions

110mm
146mm
235mm

Physical Specification

Item Group	07 Downlights Adjustable LED
Family	The Box Type Shop Range
Order Code	51140/B/W
Colour	Black
Material	Aluminium
Shape	Rectangular
Length	235mm
Width	145mm
Height	110mm
Cutout Hole Width	220mm
Cutout Hole Length	130mm
Recessed Ceiling	Yes

Depth Required	140mm
Indoor	Yes
Adjustable	1 Direction

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	☐
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
Input Current	1050mA
Voltage	35V
Safety Class	III
Power(Watts)	37W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Sanan

Gear

Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	34,65-42W
Power Factor	0,9
Constant Current	Yes
1050mA	33-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	Lifud

Illumination Data

Colour Temperature	3000K
Lumen Output	3400lm
Light Efficiency	85lm/W
CRI	80
Beam Angle	70°
Illumination Diagram	

Packing Info

Pcs/Carton	9
Barcode	5291889061458
HS Code	9405409900

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes