

## 07 Downlights Adjustable LED>The COB Box Type Shop Range

# 51230/B/C



2x30W COB LED Recessed adjustable downlight, COB square range, IP20.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



#### Downloads










#### Dimensions



185mm



105mm

### Gallery



#### **Physical Specification**

| Item Group |  |
|------------|--|
| Family     |  |
| Order Code |  |
| Colour     |  |
| Material   |  |
| Shape      |  |
| Length     |  |

|  | )7 | <b>Downlights</b> | Adjustable | LED |
|--|----|-------------------|------------|-----|
|--|----|-------------------|------------|-----|

The COB Box Type Shop Range

51230/B/C

Black

Aluminium

Rectangular

350mm

| Width                      | 185mm             |
|----------------------------|-------------------|
| Height                     | 105mm             |
| Cutout Hole Width          | 320mm             |
| Cutout Hole Length         | 160mm             |
| Recessed Ceiling           | Yes               |
| Depth Required             | 125mm             |
| Indoor                     | Yes               |
| Adjustable                 | 2 Directions      |
|                            |                   |
| Electrical Characteristics |                   |
| Gear                       | External-Included |
| - CCAI                     |                   |
| Fitting + Driver           |                   |
| Input Voltage              | 220-240V          |
| 50 Hz                      | Yes               |
| 60 Hz                      | Yes               |
| Safety Class               |                   |
| Power(Watts)               | 2x30W             |
| IP Rating                  | IP20              |
| Light Source               | LED built in      |
| Dimmable                   | No                |
| F Mark                     | F                 |
|                            |                   |
| Fitting                    |                   |
| Input Type                 | Constant Current  |
| Input Current              | 750mA             |
| Voltage                    | 2x35,5V           |
| Safety Class               |                   |
| Power(Watts)               | 2x27W             |
| IP Rating                  | IP20              |
|                            |                   |

| LED Type  | СОВ                      |
|---|--------------------------|
| LED Brand   | Sanan                    |
|   |                          |
| Gear  |                          |
| Gear Type   | Led Driver               |
| Input Voltage   | 220-240V                 |
| 50 Hz   | Yes                      |
| 60 Hz   | Yes                      |
| Power(Watts)  | 24,75-30W                |
| Power Factor  | 0,9                      |
| Constant Current  | Yes                      |
| 750mA   | 33-40V                   |
| IP Rating   | IP20                     |
| Safety Class  |                          |
| Dimmable  | No                       |
| Housing Material  | Plastic                  |
| Brand   | Lifud                    |
|   |                          |
|   |                          |
| Illumination Data   |                          |
|   | 400014                   |
| Colour Temperature  | 4000K                    |
| Colour Temperature  Lumen Output  | 2x2700lm                 |
| Colour Temperature  Lumen Output  Light Efficiency  | 2x2700lm<br>90lm/W       |
| Colour Temperature  Lumen Output  Light Efficiency  CRI   | 2x2700lm<br>90lm/W<br>90 |
| Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle   | 2x2700lm<br>90lm/W       |
| Colour Temperature  Lumen Output  Light Efficiency  CRI   | 2x2700lm<br>90lm/W<br>90 |
| Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle   | 2x2700lm<br>90lm/W<br>90 |
| Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle   | 2x2700lm<br>90lm/W<br>90 |
| Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram                           | 2x2700lm<br>90lm/W<br>90 |
| Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram                           | 2x2700lm  90lm/W  38°    |
| Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Pcs/Carton | 2x2700lm 90lm/W 90 38°   |

| Warranty       | 2 Years |  |
|----------------|---------|--|
| Weee Directive | Yes     |  |

Certification & Warranty