

### 15 Plafo>The LED Slim Plafo Range Round

# 62022C/W/W



36W LED slim plafo light, IP20, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



#### Gallery





### Physical Specification

Item Group	15 Plafo
Family	The LED Slim Plafo Range Round
Order Code	62022C/W/W
Colour	White
Material	PC
Shape	Circular
Height	75mm


Surface Ceiling	Yes
Indoor	Yes
Adjustable	No
ectrical Characteristics	
_	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	36W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	900mA
Voltage	38V
Power(Watts)	34,2W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan
LED Number	240
F Mark	F

460mm

Diameter

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	22,5-37,8W
Power Factor	0,9
Constant Current	Yes
900mA	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Lifud
Illumination Data	
Colour Temperature	3000K
Colour Temperature  Lumen Output	2900m
Colour Temperature  Lumen Output  Light Efficiency	
Colour Temperature  Lumen Output	2900m
Colour Temperature  Lumen Output  Light Efficiency	2900m 80,55lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	2900m 80,55lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	2900m 80,55lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram	2900m 80,55lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length	2900m 80,55lm/W 80 47cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width	2900m 80,55lm/W 80 47cm 47cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	2900m 80,55lm/W 80 47cm 47cm 9,5cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Box Weight	2900m 80,55lm/W 80 47cm 47cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	2900m 80,55lm/W 80 47cm 47cm 9,5cm

## Energy Label



Certification & Warranty	
Warranty	2 Years

Weee Directive

Yes