

## 15 Plafo>The LED Plafo Range Round

# 62024C/C



26W LED slim plafo light, IP20, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



#### Downloads










#### Dimensions



### Gallery






#### Physical Specification

Item Group	15 Plafo
Family	The LED Plafo Range Round
Order Code	62024C/C
Colour	White
Material	Metal
Diffuser Material	Plastic
Shape	Circular

Height	115mm
Diameter	440mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No
Electrical Characteristics	
	D. W.L.
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	26W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	36V
Power(Watts)	25,2W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD
LED Brand	Epistar
F Mark	F

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	19-29,4W
Power Factor	0,9
Constant Current	Yes
700mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise
Illumination Data	
	4000K
Colour Temperature	4000K 1600lm
	4000K 1600lm 61,53lm/W
Colour Temperature  Lumen Output	1600lm
Colour Temperature  Lumen Output  Light Efficiency	1600lm
Colour Temperature  Lumen Output  Light Efficiency  Illumination Diagram	1600lm
Colour Temperature  Lumen Output  Light Efficiency	1600lm
Colour Temperature  Lumen Output  Light Efficiency  Illumination Diagram	1600lm
Colour Temperature  Lumen Output  Light Efficiency  Illumination Diagram  Packing Info	1600lm 61,53lm/W
Colour Temperature  Lumen Output  Light Efficiency  Illumination Diagram  Packing Info  Box Length	1600lm 61,53lm/W  44cm
Colour Temperature  Lumen Output  Light Efficiency  Illumination Diagram  Packing Info  Box Length  Box Width	1600lm 61,53lm/W 44cm 44cm
Colour Temperature  Lumen Output  Light Efficiency  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	1600lm 61,53lm/W  44cm 44cm 12,5cm
Colour Temperature  Lumen Output  Light Efficiency  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Box Weight	1600lm 61,53lm/W  44cm 44cm 12,5cm 1,5kg

## Energy Label



Certification	& W	/arrantv
Columbation	$\sim$ $^{\prime}$	arrarrey

Warranty	2 Years
Weee Directive	Yes