

## 15 Plafo>LED Aluminium Panel Range

## 62140RE/W/C



40W, 120x30cm LED slim plafo light, IP40, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Din	 ~~	_	50
		Ю	



## Physical Specification

Item Group	15 Plafo
Family	LED Aluminium Panel Range
Order Code	62140RE/W/C
Colour	White
Material	Aluminium
Shape	Rectangular
Length	1200mm
Width	300mm
Height	40mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

_		
E	Actrica	l Characteristics
_	CUILGI	i Olialiautelialius

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP40
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	1000mA
Voltage	38V
Safety Class	
Power(Watts)	38W
IP Rating	IP40
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes

Power(Watts)	28,5-38W
Power Factor	0,9
Constant Current	Yes
1000mA	30-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	40°C
Operating Temp	80°C
Housing Material	Plastic
Output Terminal	Cable
Fast Connector	Yes
Fast Connector Type	Other
Brand	AGT
Illumination Data	
	4000K
Colour Temperature	4000K 3600lm
Colour Temperature  Lumen Output	3600lm
Colour Temperature  Lumen Output  Light Efficiency	3600lm 90lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	3600lm
Colour Temperature  Lumen Output  Light Efficiency	3600lm 90lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram	3600lm 90lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	3600lm 90lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram	3600lm 90lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram	3600lm 90lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length	3600lm 90lm/W 80 133cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width	3600lm 90lm/W 80 133cm 36cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	3600lm 90lm/W 80 133cm 36cm 8,5cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Box Weight	3600lm 90lm/W 80  133cm 36cm 8,5cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Box Weight  Pcs/Carton	3600lm 90lm/W 80 133cm 36cm 8,5cm 4Kg

Warranty	2 Years
Weee Directive	Yes

Certification & Warranty