

15 Plafo>LED Die Cast Panel Range

62140RF/W/C



40W LED slim plafo light, IP40, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Gallery



Accessories



050128

Trysical opecinication	
Item Group	15 Plafo
Family	LED Die Cast Panel Range
Order Code	62140RF/W/C
Colour	White
Material	Die Cast
Shape	Rectangular
Length	1200mm
Width	145mm
Height	50mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No
Electrical Characteristics Gear	External-Included
	External-Included 220-240V
Gear Fitting + Driver	
Gear Fitting + Driver Input Voltage	220-240V
Gear Fitting + Driver Input Voltage 50 Hz	220-240V Yes
Gear Fitting + Driver Input Voltage 50 Hz 60 Hz	220-240V Yes
Gear Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class	220-240V Yes Yes
Gear Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts)	220-240V Yes Yes 40W
Gear Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating	220-240V Yes Yes 40W IP40
Gear Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source	220-240V Yes Yes U 40W IP40 LED built in
Gear Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source Dimmable	220-240V Yes Yes U 40W IP40 LED built in
Gear Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source Dimmable	220-240V Yes Yes U 40W IP40 LED built in
Gear Fitting + Driver Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source Dimmable F Mark	220-240V Yes Yes U 40W IP40 LED built in

Voltage	38V
Safety Class	
Power(Watts)	38W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2016
LED Brand	Sanan
LED Number	300
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	30-40W
Power Factor	0,9
Constant Current	Yes
1000mA	30-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	40°C
Operating Temp	80°C
Housing Material	Plastic
Output Terminal	Cable
Output Terminal Fast Connector	


ONE Light

Brand

Colour Temperature	4000K
Lumen Output	2700lm
Light Efficiency	67,5lm/W
CRI	80
Illumination Diagram	

Box Weight 4,3kg Pcs/Carton 5 Barcode 5291889049906 HS Code 9405409900

Energy Label



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes