



80W LED Pendant , IP20 suitable for residential and commercial application .

Complete with 1000mA drivers.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

| | |
|-------------------|-------------------|
| Item Group | 18 Decorative |
| Family | LED Pendant Rings |
| Order Code | 62180NB/W/W |
| Colour | White |
| Material | Aluminium |
| Shape | Circular |
| Height | 1500mm |
| Diameter | 780mm |
| Suspended Ceiling | Yes |
| Indoor | Yes |
| Adjustable | No |

Gear

Built In

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

80W

IP Rating

IP20

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

1000mA

Voltage

2x38V

Power(Watts)

2x38W

IP Rating

IP20

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Epistar

F Mark



Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz


Yes

60 Hz


Yes

Power(Watts)

27-42W

| | |
|------------------|---|
| Power Factor | 0,9 |
| Constant Current | Yes |
| 1000mA | 27-42V |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Housing Material | Plastic |
| Output Terminal | Cable |
| Brand | Lifud |

Illumination Data

| | |
|----------------------|---|
| Colour Temperature | 3000K |
| Lumen Output | 4400lm |
| Light Efficiency | 55lm/W |
| CRI | 80 |
| Illumination Diagram |  |

Packing Info

| | |
|------------|---------------|
| Pcs/Carton | 1 |
| Barcode | 5291889062776 |
| HS Code | 9405409900 |

Energy Label



Warranty

2 Years

Weee Directive

Yes
