



100W SMD LED Industrial High Bay, IP65.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



### Downloads



### Dimensions



### Gallery





### Physical Specification

Item Group	21 Industrial & Floodlights
Family	The Industrial IP65 LED UFO Range Aluminium
Order Code	63100N/C
Colour	Black
Material	Aluminium
Shape	Circular
Height	160mm

Diameter	250mm
Surface Ceiling	Yes
Surface Wall	Yes
Suspended Ceiling	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No

## Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	100W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
Cable Length	30cm
F Mark	

Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	190V
Power(Watts)	95W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835

LED Brand

Osram

Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

90-130W

Power Factor

0,9

Constant Current

Yes

500mA

180-260V

IP Rating

IP65

Safety Class



Brand

Lifud

Illumination Data

Colour Temperature

4000K

Lumen Output

13000lm

Light Efficiency

130lm/W

CRI

80

Beam Angle

90°

Illumination Diagram



Packing Info

Pcs/Carton

1

Barcode

5291889067948

HS Code

9405409900

Warranty

---

5 Years

---

Weee Directive

---

Yes

---