



150W SMD LED Industrial High Bay, IP65.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



### Downloads



### Dimensions



### Gallery





### Physical Specification


Item Group	21 Industrial & Floodlights
Family	The Industrial IP65 LED UFO Range Aluminium
Order Code	63150N/C
Colour	Black
Material	Aluminium
Shape	Circular
Height	170mm

Diameter	300mm
Surface Ceiling	Yes
Surface Wall	Yes
Suspended Ceiling	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No


## Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	150W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
Cable Length	30cm
F Mark	

Fitting	
Input Type	Constant Current
Input Current	750mA
Voltage	190V
Power(Watts)	142,5W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835

LED Brand	Osram
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	135-195W
Power Factor	0,9
Constant Current	Yes
750mA	180-260V
IP Rating	IP65
Safety Class	
Brand	Lifud

#### Illumination Data

Colour Temperature	4000K
Lumen Output	19500lm
Light Efficiency	130lm/W
CRI	80
Beam Angle	90°
Illumination Diagram	

#### Packing Info

Pcs/Carton	1
Barcode	5291889067955
HS Code	9405409900

Warranty

---

5 Years

---

Weee Directive

---

Yes

---