

## 10 Track Spots>Adjustable LED Linear Track Light

# 65024T/B/W



10X5W COB linear track light spot +-45° adjustable, ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.











#### Downloads









#### Dimensions



### Related items







40003A/B

### **Physical Specification**

| Item Group | 10 Track Spots                    |
|------------|-----------------------------------|
| Family     | Adjustable LED Linear Track Light |
| Order Code | 65024T/B/W                        |
| Colour     | Black                             |
| Material   | Aluminium + Plastic               |
| Shape      | Rectangular                       |
| Length     | 580mm                             |

| Width         | 60mm        |
|---------------|-------------|
| Height        | 80mm        |
| Track mounted | Yes         |
| Indoor        | Yes         |
| Adjustable    | 1 Direction |
|               |             |
|               |             |

#### **Electrical Characteristics**

| Electrical Characteristics |                  |
|----------------------------|------------------|
| Gear                       | Built In         |
|                            |                  |
| Fitting + Driver           |                  |
| Input Voltage              | 220-240V         |
| 50 Hz                      | Yes              |
| 60 Hz                      | Yes              |
| Safety Class               |                  |
| Power(Watts)               | 10x5W            |
| IP Rating                  | IP20             |
| Light Source               | LED built in     |
| Dimmable                   | No               |
|                            |                  |
| Fitting                    |                  |
| Input Type                 | Constant Current |
| Input Current              | 1200mA           |
| Voltage                    | 38V              |
| Power(Watts)               | 45,6W            |
| IP Rating                  | IP20             |
| Light Source               | LED built in     |
| LED Type                   | COB              |
| LED Brand                  | Bridgelux        |
| LED Number                 | 10               |
|                            |                  |


Gear

| Input Voltage  | 220-240V                                       |
|--|--|
|  |  |
| 50 Hz  | Yes  |
| 60 Hz  | Yes  |
| Power(Watts)   | 39,6-50,4W                                     |
| Power Factor   | 0,9  |
| Constant Current   | Yes  |
| 1200mA   | 33-42V   |
| IP Rating  | IP20   |
| Safety Class   |  |
| Dimmable   | No   |
| Housing Material   | Plastic  |
| Output Terminal  | Connector                                      |
| Brand  | LIFUD  |
| Protection   | Short Circuit Protection                       |
|  |  |
|  |  |
|  |  |
| llumination Data   |  |
| Ilumination Data  Colour Temperature   | 3000K  |
|  | 3000K<br>10x580lm                              |
| Colour Temperature   |  |
| Colour Temperature  Lumen Output   | 10x580lm                                       |
| Colour Temperature  Lumen Output  Light Efficiency   | 10x580lm<br>116lm/W                            |
| Colour Temperature  Lumen Output  Light Efficiency  CRI  | 10x580lm<br>116lm/W<br>80                      |
| Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  | 10x580lm<br>116lm/W<br>80                      |
| Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram                                      | 10x580lm<br>116lm/W<br>80                      |
| Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram                                      | 10x580lm<br>116lm/W<br>80                      |
| Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram                                      | 10x580lm<br>116lm/W<br>80                      |
| Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram                                      | 10x580lm  116lm/VV  80  30°                    |
| Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length            | 10x580lm  116lm/W  80  30°  51,5cm             |
| Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width | 10x580lm  116lm/W  80  30°  51,5cm  9cm        |
| Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height         | 10x580lm  116lm/VV  80  30°  51,5cm  9cm  13cm |

Led Driver

Gear Type

# Energy Label



| Energy Class       | D           |
|--------------------|-------------|
| Energy Consumption | 50KWh/1000h |

### Certification & Warranty

| Warranty       | 2 Years |
|----------------|---------|
| Weee Directive | Yes     |