

10 Track Spots>Adjustable LED Linear Track Light

65026T/B/C



40W COB linear track light spot +-45° adjustable, ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads









Dimensions



Related items







40003A/B

Physical Specification

Item Group	10 Track Spots
Family	Adjustable LED Linear Track Light
Order Code	65026T/B/C
Colour	Black
Material	Aluminium + Plastic
Shape	Rectangular
Length	500mm

Width	60mm
Height	100mm
Track mounted	Yes
Indoor	Yes
Adjustable	1 Direction
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	1000mA
Voltage	38V
Power(Watts)	38W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan
Gear	
Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	28-40W
Power Factor	0,9
Constant Current	Yes
1000mA	28-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	BOKE
Protection	Short Circuit Protection
llumination Data	
	4000K
Colour Temperature	4000K 3400lm
Colour Temperature Lumen Output	3400lm
Colour Temperature Lumen Output Light Efficiency	3400lm 85lm/W
Colour Temperature Lumen Output Light Efficiency CRI	3400lm 85lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3400lm 85lm/W
Colour Temperature Lumen Output Light Efficiency CRI	3400lm 85lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3400lm 85lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3400lm 85lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3400lm 85lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3400lm 85lm/W 80 100°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	3400lm 85lm/W 80 100° 51,5cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	3400lm 85lm/W 80 100° 51,5cm 9cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	3400lm 85lm/W 80 100° 51,5cm 9cm 13cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height Pcs/Carton	3400lm 85lm/W 80 100° 51,5cm 9cm 13cm

Warranty	2 Years
Weee Directive	Yes

Certification & Warranty