

## 10 Track Spots>The Track Floodlight Range

# 65040T/W/C



40W COB LED track spot with, ideal for shops and showrooms.

Complete with 1050mA driver.

Complies with standard EN60598-1 and any other specific standards.



#### Downloads










#### Dimensions



#### Related items







40003A/W

### **Physical Specification**

Item Group	10 Track Spots
Family	The Track Floodlight Range
Order Code	65040T/W/C
Colour	White
Material	Aluminium
Shape	Rectangular
Length	225mm

Width	110mm
Height	220mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions


#### Electrical Characteristics

Built In	lectrical Characteristics	
Input Voltage         220-240V           50 Hz         Yes           60 Hz         Yes           Safety Class         □           Power(Watts)         40W           IP Rating         IP20           Light Source         LED built in           Dimmable         No           Fitting           Input Type         Constant Current           Input Current         1050mA           Voltage         36V           Power(Watts)         37,8W           IP Rating         IP20           Light Source         LED built in           LED Type         COB           LED Brand         Sanan	Gear	Built In
Input Voltage         220-240V           50 Hz         Yes           60 Hz         Yes           Safety Class         □           Power(Watts)         40W           IP Rating         IP20           Light Source         LED built in           Dimmable         No           Fitting           Input Type         Constant Current           Input Current         1050mA           Voltage         36V           Power(Watts)         37,8W           IP Rating         IP20           Light Source         LED built in           LED Type         COB           LED Brand         Sanan		
So Hz  Fitting  Input Type  Constant Current  Input Current  Input Current  Voltage  Power(Watts)  IP Rating  IP 20  LED built in  No  Fitting  Input Type  Constant Current  Input Current  Input Current  Input Current  Input Current  IP Rating  IP Power(Watts)  IP Rating  IP Rating  IP COB  LED Brand  Sanan	Fitting + Driver	
Safety Class  Power(Watts)  IP Rating  Light Source  Dimmable  Fitting  Input Type  Constant Current  Input Current  1050mA  Voltage  36V  Power(Watts)  IP Rating  IP PRating  IP PRating  IP PRating  IP COB  LED Brand  Sanan	Input Voltage	220-240V
Safety Class  Power(Watts)  IP Rating  Light Source  LED built in  No  Fitting  Input Type  Constant Current  Input Current  1050mA  Voltage  Power(Watts)  IP Rating  IP PRating  IP PRating  IP PRATING  LED built in  COB  LED Brand  Sanan	50 Hz	Yes
Power(Watts)         40W           IP Rating         IP20           Light Source         LED built in           Dimmable         No    Fitting  Input Type  Constant Current  1050mA  Voltage  36V  Power(Watts)  37,8W  IP Rating  IP20  Light Source  LED built in  LED Type  COB  Sanan	60 Hz	Yes
IP Rating         IP20           Light Source         LED built in           Dimmable         No    Fitting  Input Type  Constant Current  1050mA  Voltage  36V  Power(Watts)  37,8W  IP Rating  IP20  Light Source  LED built in  LED Type  COB  LED Brand  Sanan	Safety Class	
Light Source  Dimmable  No  Fitting  Input Type  Constant Current  1050mA  Voltage  36V  Power(Watts)  IP Rating  LED built in  LED built in  COB  LED Brand  Sanan	Power(Watts)	40W
Fitting  Input Type Constant Current  Input Current 1050mA  Voltage 36V  Power(Watts) 37,8W  IP Rating IP20  Light Source LED built in  LED Type COB  LED Brand Sanan	IP Rating	IP20
Fitting  Input Type Constant Current  Input Current 1050mA  Voltage 36V  Power(Watts) 37,8W  IP Rating IP20  Light Source LED built in  LED Type COB  LED Brand Sanan	Light Source	LED built in
Input Type         Constant Current           Input Current         1050mA           Voltage         36V           Power(Watts)         37,8W           IP Rating         IP20           Light Source         LED built in           LED Type         COB           LED Brand         Sanan	Dimmable	No
Input Type         Constant Current           Input Current         1050mA           Voltage         36V           Power(Watts)         37,8W           IP Rating         IP20           Light Source         LED built in           LED Type         COB           LED Brand         Sanan		
Input Current         1050mA           Voltage         36V           Power(Watts)         37,8W           IP Rating         IP20           Light Source         LED built in           LED Type         COB           LED Brand         Sanan	Fitting	
Voltage36VPower(Watts)37,8WIP RatingIP20Light SourceLED built inLED TypeCOBLED BrandSanan	Input Type	Constant Current
Power(Watts)  IP Rating  Light Source  LED built in  COB  LED Brand  Sanan	Input Current	1050mA
IP RatingIP20Light SourceLED built inLED TypeCOBLED BrandSanan	Voltage	36V
Light SourceLED built inLED TypeCOBLED BrandSanan	Power(Watts)	37,8W
LED Type COB  LED Brand Sanan	IP Rating	IP20
LED Brand Sanan	Light Source	LED built in
	LED Type	СОВ
I ED Monakan	LED Brand	Sanan
LED Number	LED Number	1

Gear

	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	31,5-44,1W
Power Factor	0,9
Constant Current	Yes
1050mA	30-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Lifud
Ilumination Data	
Colour Temperature	4000K
Colour Temperature  Lumen Output	4000K 3600lm
Lumen Output	3600lm
Lumen Output Light Efficiency	3600lm 90lm/W
Lumen Output Light Efficiency CRI	3600lm 90lm/W 90
Lumen Output  Light Efficiency  CRI  Beam Angle	3600lm 90lm/W 90
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	3600lm 90lm/W 90
Lumen Output  Light Efficiency  CRI  Beam Angle	3600lm 90lm/W 90
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	3600lm 90lm/W 90
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	3600lm 90lm/W 90 60°
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Pcs/Carton	3600lm 90lm/W 90 60°

## Energy Label



Certification & Warranty		

Warranty	3 Years
Weee Directive	Yes