

### 10 Track Spots>Mirror Square Track Spots

## 65306BT/W/W



12W track spot with COB LED.

Complete with 300mA driver.

Complies with standard EN60598-1 and any other specific standards.



### Downloads










#### Dimensions



#### Related items







40003A/W

#### Physical Specification

Item Group	10 Track Spots
Family	Mirror Square Track Spots
Order Code	65306BT/W/W
Colour	White
Material	Die Cast
Shape	Rectangular
Length	54mm

Width	42mm
Height	118mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions

# Electrical Characteristics


Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	12W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	300mA
Voltage	38V
Power(Watts)	10,4W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Cree
LED Number	3

Gear

	Led Driver		
Input Voltage	220-240V		
50 Hz	Yes		
60 Hz	Yes		
Power(Watts)	7,5-12,4W		
Power Factor	0,9		
Constant Current	Yes		
300mA	25-42V		
IP Rating	IP20		
Safety Class			
Dimmable	No		
Housing Material	Plastic		
Output Terminal	Connector		
Brand	Lifud		
Protection	Short Circuit Protection		
Illumination Data  Colour Temperature	3000K		
	3000K 960lm		
Colour Temperature			
Colour Temperature  Lumen Output	960lm		
Colour Temperature  Lumen Output  Light Efficiency	960lm 80lm/W		
Colour Temperature  Lumen Output  Light Efficiency  CRI	960lm 80lm/W 90		
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	960lm 80lm/W 90		
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	960lm 80lm/W 90		
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	960lm  80lm/W  90  38°		
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length	960lm 80lm/W 90 38°  18,5cm		
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width	960lm  80lm/W  90  38°  18,5cm  12,3cm		
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	960lm  80lm/W  90  38°  18,5cm  12,3cm  4,5cm		
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Pcs/Carton	960lm 80lm/W 90 38°  18,5cm 12,3cm 4,5cm		
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	960lm  80lm/W  90  38°  18,5cm  12,3cm  4,5cm		

3 Years

## Energy Label



Warranty

Certification & Warranty		

Weee Directive Yes