


09 Track Lights>The COB Compact Cylinder Range

65524T/B/W



12W COB track spot with honeycomb.

Complete with 250mA driver.

Complies with standard EN60598-1 and any other specific standards.









Downloads









Dimensions



Related items







40003A/B

Physical Specification

Item Group	09 Track Lights
Family	The COB Compact Cylinder Range
Order Code	65524T/B/W
Colour	Black
Material	Aluminium
Shape	Circular
Height	110mm
Material Shape	Aluminium Circular

Diameter	55mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
lectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	12W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	250mA
Voltage	48V
Power(Watts)	12W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Sanan
Gear	
Gear Type	Led Driver

220-240V

Input Voltage

50 Hz	Yes
60 Hz	Yes
Power(Watts)	12W
Power Factor	0,9
Constant Current	Yes
250mA	48
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Lifud
	Short Circuit Protection
Protection	
Illumination Data Colour Temperature	3000K
Illumination Data	3000K 1080lm
Illumination Data Colour Temperature	
Illumination Data Colour Temperature Lumen Output	1080lm
Illumination Data Colour Temperature Lumen Output Light Efficiency	1080lm 90lm/W
Colour Temperature Lumen Output Light Efficiency CRI	1080lm 90lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	1080lm 90lm/W 90 36°
Illumination Data Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1080lm 90lm/VV 90 36°
Illumination Data Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1080lm 90lm/VV 90 36°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light	1080lm 90lm/W 90 36° Yes
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Pcs/Carton	1080lm 90lm/W 90 36° Yes
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Pcs/Carton Barcode	1080lm 90lm/W 90 36° Yes 24 5291889063391
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Pcs/Carton	1080lm 90lm/W 90 36° Yes

Warranty	3 Years
Weee Directive	Yes

Certification & Warranty