

10 Track Spots>The COB Track Spot Range Aluminium

65612NT/W/W



30W track spot with COB LED, ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Related items







40003A/W

Physical Specification

10 Track Spots
The COB Track Spot Range Aluminium
65612NT/W/W
White
Aluminium
Circular
123mm

Diameter	90mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
ectrical Characteristics	
Gear	Built In
Fitting , Driver	
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	750mA
Voltage	38V
Safety Class	
Power(Watts)	28,5W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Bridgelux
Gear	
Gear Type	Led Driver

50 I I-	Vac
50 Hz	Yes
60 Hz	Yes
Power(Watts)	25-30W
Power Factor	0,9
Constant Current	Yes
750mA	33-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Lifud
Protection	Short Circuit Protection
llumination Data	
Colour Temperature	3000K
Colour Temperature Lumen Output	3000K 2400lm
Lumen Output	2400lm
Lumen Output Light Efficiency	2400lm 80lm/W
Lumen Output Light Efficiency CRI	2400lm 80lm/W 90
Lumen Output Light Efficiency CRI Beam Angle	2400lm 80lm/W 90
Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	2400lm 80lm/W 90
Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	2400lm 80lm/W 90
Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	2400lm 80lm/W 90
Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	2400lm 80lm/W 90 38°
Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	2400lm 80lm/W 90 38°
Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	2400lm 80lm/W 90 38° 25cm 10cm
Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	2400lm 80lm/W 90 38° 25cm 10cm
Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height Pcs/Carton	2400lm 80lm/W 90 38° 25cm 10cm 10cm

220-240V

Input Voltage

Warranty	2 Years
Average Lifetime	30000 hours
Weee Directive	Yes

Certification & Warranty