

09 Track Lights>The COB Track Spot Range Aluminium

65614NT/W/C



42W track spot with COB LED, ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Related items







40003A/W

Physical Specification

09 Track Lights
The COB Track Spot Range Aluminium
65614NT/W/C
White
Aluminium
Circular
128mm

Diameter	100mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	42W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	1050mA
Voltage	38V
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Sanan
Gear	
Gear Type	Led Driver

Input Voltage	220-240V	
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	35-42W	
Power Factor	0,9	
Constant Current	Yes	
1050mA	33-40V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Connector	
Brand	Lifud	
	Short Circuit Protection	
Protection umination Data		
umination Data		
umination Data Colour Temperature	4000K	
umination Data Colour Temperature Lumen Output	4000K 3500lm	
umination Data Colour Temperature Lumen Output Light Efficiency	4000K 3500lm 83,33lm/W	
umination Data Colour Temperature Lumen Output Light Efficiency CRI	4000K 3500lm 83,33lm/W 90	
umination Data Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	4000K 3500lm 83,33lm/W	
umination Data Colour Temperature Lumen Output Light Efficiency CRI	4000K 3500lm 83,33lm/W 90	
umination Data Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	4000K 3500lm 83,33lm/W 90	
umination Data Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	4000K 3500lm 83,33lm/W 90	
umination Data Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	4000K 3500lm 83,33lm/W 90	
umination Data Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	4000K 3500lm 83,33lm/W 90 38°	
umination Data Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram acking Info Box Length	4000K 3500lm 83,33lm/W 90 38°	
umination Data Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram acking Info Box Length Box Width	4000K 3500lm 83,33lm/W 90 38° 25cm	
umination Data Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram acking Info Box Length Box Width Box Height	4000K 3500lm 83,33lm/W 90 38° 25cm 15cm 10,5cm	

Warranty	2 Years
Weee Directive	Yes

Certification & Warranty