

10 Track Spots>The COB Top Box Range

65624T/W/C



35W track spot with COB LED, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Gallery



Related items





40002A/W 40003A/W

Physical Specification

Item Group

10 Track Spots

Family

The COB Top Box Range

| Order Code | 65624T/W/C |
|----------------------------|--------------|
| Colour | White |
| Material | Die Cast |
| Shape | Circular |
| Height | 123mm |
| Diameter | 106mm |
| Track mounted | Yes |
| Indoor | Yes |
| Adjustable | 2 Directions |
| | |
| Electrical Characteristics | |

| Electrical Characteristics | |
|----------------------------|------------------|
| Gear | Built In |
| Fitting + Driver | |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class | |
| Power(Watts) | 35W |
| IP Rating | IP20 |
| Light Source | LED built in |
| Dimmable | No |
| Fitting | |
| Input Type | Constant Current |
| Input Current | 900mA |
| Voltage | 38V |
| Power(Watts) | 34,2W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | СОВ |
| | |


| Gear Type Led Driver Input Voltage 220-240V 50 Hz Yes 60 Hz Yes Power(Watts) 25-50W Power Factor 0,9 Constant Current Yes 900mA 27-54V IP Rating IP20 Safety Class □ Dimmable No Ambient Temp 50°C Operating Temp 80°C Housing Material Plastic |
|---|
| Input Voltage 220-240V 50 Hz Yes 60 Hz Yes Power(Watts) 25-50W Power Factor 0,9 Constant Current Yes 900mA 27-54V IP Rating IP20 Safety Class ID Dimmable No Ambient Temp 50°C Operating Temp 80°C Housing Material Plastic |
| Yes 60 Hz Yes Power(Watts) Power Factor O,9 Constant Current Yes 900mA 27-54V IP Rating IP20 Safety Class Dimmable No Ambient Temp Operating Temp Housing Material Yes Yes Yes 19-20 No No Residuate Son C Plastic |
| Yes Power (Watts) 25-50W |
| Power(Watts) 25-50W Power Factor 0,9 Constant Current Yes 900mA 27-54V IP Rating IP20 Safety Class □ Dimmable No Ambient Temp 50°C Operating Temp 80°C Housing Material Plastic |
| Power Factor Constant Current Yes 900mA 27-54V IP Rating IP20 Safety Class Dimmable No Ambient Temp Operating Temp Housing Material No,9 Yes Yes No 27-54V No Answer Plastic |
| Constant Current 900mA 27-54V IP Rating IP20 Safety Class Dimmable Ambient Temp Operating Temp Housing Material Yes 27-54V IP20 No Plastic |
| 900mA 27-54V IP Rating IP20 Safety Class |
| IP Rating Safety Class Dimmable Ambient Temp Operating Temp Housing Material IP20 No IP20 No No No Plastic |
| Safety Class Dimmable Ambient Temp Operating Temp Housing Material Dimmable No 80°C Plastic |
| Dimmable Ambient Temp 50°C Operating Temp 80°C Housing Material Plastic |
| Ambient Temp 50°C Operating Temp 80°C Housing Material Plastic |
| Operating Temp Housing Material Plastic |
| Housing Material Plastic |
| |
| Outrant Tampinal |
| Output Terminal Connector |
| Brand Philips |
| Protection Short Circuit Protection |
| |
| umination Data |
| Colour Tomporature |
| Colour Temperature 4000K Lumen Output 3050lm |
| |
| Light Efficiency 87,14lm/W CRI 80 |
| Beam Angle 45° |
| Illumination Diagram |

Cree

LED Brand

| Box Weight | 1,6kg |
|------------|---------------|
| Pcs/Carton | 12 |
| Barcode | 5291889043485 |
| HS Code | 9405409900 |

Energy Label



Certification & Warranty

| Warranty | 3 Years |
|------------------|------------|
| Average Lifetime | 40000hours |
| Weee Directive | Yes |