

10 Track Spots>The COB Cylinder Range

65632CT/B/W



50W track spot with COB LED, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Related items







40003A/B

Physical Specification


| Item Group | 10 Track Spots |
|------------|------------------------|
| Family | The COB Cylinder Range |
| Order Code | 65632CT/B/W |
| Colour | Black |
| Material | Die Cast |
| Shape | Circular |
| Height | 160mm |

| Diameter | 130mm |
|----------------------------|------------------|
| Track mounted | Yes |
| Indoor | Yes |
| Adjustable | 2 Directions |
| | |
| Electrical Characteristics | |
| | |
| Gear | Built In |
| | |
| Fitting + Driver | |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class | |
| Power(Watts) | 50W |
| IP Rating | IP20 |
| Light Source | LED built in |
| Dimmable | No |
| | |
| Fitting | |
| Input Type | Constant Current |
| Input Current | 1250mA |
| Voltage | 37V |
| Safety Class | (III) |
| Power(Watts) | 46,25W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | СОВ |
| LED Brand | Cree |
| | |
| Gear | |
| Gear Type | Led Driver |
| | |

| Input Voltage | 220-240V |
|--|---------------------------------|
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 24-52,5W |
| Power Factor | 0,9 |
| Constant Current | Yes |
| 1250mA | 37-42V |
| IP Rating | IP20 |
| Safety Class | |
| Dimmable | No |
| Ambient Temp | -20~50°C |
| Operating Temp | 90°C |
| Housing Material | Plastic |
| Output Terminal | Connector |
| Brand | Tridonic |
| Protection | Short Circuit Protection |
| | |
| | |
| Illumination Data | |
| Illumination Data | |
| Illumination Data Colour Temperature | 3000K |
| | 3000K 3750lm |
| Colour Temperature | |
| Colour Temperature Lumen Output | 3750lm |
| Colour Temperature Lumen Output Light Efficiency | 3750lm 75lm/W |
| Colour Temperature Lumen Output Light Efficiency CRI | 3750lm 75lm/W 80 |
| Colour Temperature Lumen Output Light Efficiency CRI Beam Angle | 3750lm 75lm/W 80 |
| Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram | 3750lm 75lm/W 80 |
| Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram | 3750lm 75lm/W 80 |
| Colour Temperature Lumen Output Light Efficiency CRI Beam Angle | 3750lm 75lm/W 80 |
| Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram | 3750lm 75lm/W 80 36° |
| Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length | 3750lm 75lm/W 80 36° 32,5cm |
| Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width | 3750lm 75lm/W 80 36° 32,5cm |

| Pcs/Carton | 6 |
|------------|---------------|
| Barcode | 5291889047773 |
| HS Code | 9405409900 |

Energy Label



Certification & Warranty

| Warranty | 2 Years |
|------------------|------------|
| Average Lifetime | 30000hours |
| Weee Directive | Yes |