



36W track spot with COB LED, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Related items



0740/15



40002A/W



40003A/W

Physical Specification

Item Group

10 Track Spots

Family

The COB Dark Light Cylinder Range Die cast

Order Code

65640BT/W/W

Colour

White

Material

Die Cast

Diffuser Material


Acrylic


Shape

Circular


Height	130mm
Diameter	98mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions

Electrical Characteristics


Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	36W
IP Rating	IP20
Light Source	LED built in
Dimmable	No

Fitting	
Input Type	Constant Current
Input Current	900mA
Voltage	37V
Safety Class	
Power(Watts)	33,3W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	32,4-39,6W
Power Factor	0,5
Constant Current	Yes
900mA	36-44V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°C
Operating Temp	80°C
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise
Protection	Short Circuit Protection

Illumination Data


Colour Temperature	3000K
Lumen Output	2400lm
Light Efficiency	66,67lm/W
CRI	80
Beam Angle	36°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Length	24cm
Box Width	17,5cm

Box Height	11cm
Box Weight	1,3kg
Pcs/Carton	16
Barcode	5291889047810
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes