

# 09 Track Lights>The COB Cylinder Track Spot

# 65642AT/B/C



10W track spot with COB LED, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.



#### Downloads









#### Dimensions



## Gallery



#### Related items







40003A/B

## Physical Specification

Item Group

09 Track Lights

Family

The COB Cylinder Track Spot

| Order Code                 | 65642AT/B/C  |
|----------------------------|--------------|
| Colour                     | Black        |
| Material                   | Aluminium    |
| Shape                      | Circular     |
| Height                     | 147mm        |
| Diameter                   | 55mm         |
| Track mounted              | Yes          |
| Indoor                     | Yes          |
| Adjustable                 | 2 Directions |
|                            |              |
| Electrical Characteristics |              |

| Electrical Characteristics |                  |
|----------------------------|------------------|
| Gear                       | Built In         |
| Fitting + Driver           |                  |
| Input Voltage              | 220-240V         |
| 50 Hz                      | Yes              |
| 60 Hz                      | Yes              |
| Safety Class               |                  |
| Power(Watts)               | 10W              |
| IP Rating                  | IP20             |
| Light Source               | LED built in     |
| Dimmable                   | No               |
|                            |                  |
| Fitting                    |                  |
| Input Type                 | Constant Current |
| Input Current              | 250mA            |
| Voltage                    | 38V              |
| Safety Class               | ₹III>            |
| Power(Watts)               | 9,5W             |
| IP Rating                  | IP20             |
| Light Source               | LED built in     |

| LED Type             | СОВ                      |
|----------------------|--------------------------|
| LED Brand            | Sanan                    |
|                      |                          |
| Gear                 |                          |
| Gear Type            | Led Driver               |
| Input Voltage        | 220-240V                 |
| 50 Hz                | Yes                      |
| 60 Hz                | Yes                      |
| Power(Watts)         | 6-10W                    |
| Power Factor         | 0,9                      |
| Constant Current     | Yes                      |
| 250mA                | 25-40V                   |
| IP Rating            | IP20                     |
| Safety Class         |                          |
| Dimmable             | No                       |
| Ambient Temp         | 50°C                     |
| Operating Temp       | 80°C                     |
| Housing Material     | Plastic                  |
| Output Terminal      | Connector                |
| Brand                | Lifud                    |
| Protection           | Short Circuit Protection |
|                      |                          |
| Ilumination Data     |                          |
|                      |                          |
| Colour Temperature   | 4000K                    |
| Lumen Output         | 900lm                    |
| Light Efficiency     | 90lm/W                   |
| CRI                  | 90                       |
| Beam Angle           | 38°                      |
| Illumination Diagram |                          |
|                      |                          |

| Box Length | 22cm          |
|------------|---------------|
| Box Width  | 8,5cm         |
| Box Height | 8,5cm         |
| Box Weight | 0,482kg       |
| Pcs/Carton | 24            |
| Barcode    | 5291889053897 |
| HS Code    | 9405409900    |

| Certification | & W | arranty/ |
|---------------|-----|----------|
|---------------|-----|----------|

| Warranty         | 2 Years    |
|------------------|------------|
| Average Lifetime | 30000hours |
| Weee Directive   | Yes        |