

## 20 Garden & Underwater>The LED Bollards Range Die cast

# 67034/G/W



15W LED Bollard, IP54 for Garden illumination.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



### Downloads










#### Dimensions



#### **Physical Specification**


Item Group	20 Garden & Underwater
Family	The LED Bollards Range Die cast
Order Code	67034/G/W
Colour	Grey
Material	Die Cast
Diffuser Material	PC
Shape	Circular
Height	850mm
Diameter	120mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No

## Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	350mA
Voltage	40V
Power(Watts)	14W
IP Rating	IP54
Light Source	LED built in
LED Brand	Cree
Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	13-15W

Power Factor	0,9
Constant Current	Yes
350mA	37-43V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20~55°C
Housing Material	Plastic
Output Terminal	Connector
Brand	HEP
Protection	Short Circuit
lumination Data	
Colour Temperature	3000K
Lumen Output	450lm
Light Efficiency	30lm/W
CRI	80
Beam Angle	50°
Illumination Diagram	
acking Info	
Box Length	88,5cm
Box Width	14,5cm
Box Height	14,5cm
Box Weight	4,2Kg
Pcs/Carton	4
Barcode	5291889039150
HS Code	9405409900

# Energy Label



Certification & V	<b>Varranty</b>
-------------------	-----------------

Warranty	2 Years
Average Lifetime	30000hours
Weee Directive	Yes