

### 15 Plafo>The LED Plafo Outdoor Round

# 67280BN/W/W



30W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads









#### Dimensions




#### **Physical Specification**

Item Group	15 Plafo
Family	The LED Plafo Outdoor Round
Order Code	67280BN/W/W
Colour	White
Material	Plastic
Diffuser Material	PC
Shape	Circular
Height	83mm
Diameter	360mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes

Adjustable	No
IK Rating	8
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	38V
Power(Watts)	28W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	144
F Mark	F
Gear	
Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	18,2-30W
Power Factor	0,9
Constant Current	Yes
700mA	26-43,5V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise
Illumination Data	
Illumination Data	
Illumination Data  Colour Temperature	3000K
	3000K 1800lm
Colour Temperature	
Colour Temperature  Lumen Output	1800lm
Colour Temperature  Lumen Output  Light Efficiency	1800lm 60lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	1800lm 60lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram	1800lm 60lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	1800lm 60lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram	1800lm 60lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram	1800lm 60lm/VV 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length	1800lm 60lm/W 80 7
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width	1800lm 60lm/W 80  37cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	1800lm 60lm/W 80 37cm 37cm 9cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Box Weight	1800lm 60lm/W 80 37cm 37cm 9cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Box Weight  Pcs/Carton	1800lm 60lm/W 80 37cm 9cm 1,7Kg 5

## Energy Label



Certification & Warranty	
Warranty	2 Years
Weee Directive	Yes