

15 Plafo>The LED Plafo Outdoor Round

67280N/AN/W



16W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads









Dimensions




Physical Specification

Item Group	15 Plafo
Family	The LED Plafo Outdoor Round
Order Code	67280N/AN/W
Colour	Anthracite
Material	Plastic
Diffuser Material	PC
Shape	Circular
Height	75mm
Diameter	260mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes

Adjustable	No
IK Rating	8
Electrical Characteristics	
Electrical Orlandsteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	16W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	30V
Power(Watts)	15W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	81
F Mark	F
Gear	
Gear Type	Led Driver

Input Voltage	220-240V	
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	8,5-16W	
Power Factor	0,9	
Constant Current	Yes	
500mA	19-32V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Connector	
	Eaglerise	
Brand Ilumination Data		
llumination Data	3000K	
llumination Data Colour Temperature	3000K 960lm	
llumination Data		
llumination Data Colour Temperature Lumen Output	960lm	
Colour Temperature Lumen Output Light Efficiency	960lm 60lm/W	
Colour Temperature Lumen Output Light Efficiency CRI	960lm 60lm/W	
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	960lm 60lm/W	
Colour Temperature Lumen Output Light Efficiency CRI	960lm 60lm/W	
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	960lm 60lm/W	
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	960lm 60lm/W 80	
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length	960lm 60lm/W 80 27cm	
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width	960lm 60lm/W 80 27cm 27cm	
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height	960lm 60lm/W 80 27cm 27cm 8cm	
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight	960lm 60lm/W 80 27cm 27cm 8cm 0,9Kg	

Energy Label



Certification & Warranty	
Warranty	2 Years
Weee Directive	Yes