

15 Plafo>The LED Plafo Outdoor Round

67280N/W/W



16W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.





















Dimensions




Physical Specification

Item Group	15 Plafo
Family	The LED Plafo Outdoor Round
Order Code	67280N/W/W
Colour	White
Material	Plastic
Diffuser Material	PC
Shape	Circular
Height	75mm
Diameter	260mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes

Adjustable	No
IK Rating	8
Electrical Characteristics	
Electrical Orlandsteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	16W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	30V
Power(Watts)	15W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	81
F Mark	F
Gear	
Gear Type	Led Driver

Input Voltage	220-240V	
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	8,5-16W	
Power Factor	0,9	
Constant Current	Yes	
500mA	19-32V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Connector	
	Eaglerise	
Brand Ilumination Data		1
		•
Ilumination Data Colour Temperature	3000K	
Ilumination Data Colour Temperature Lumen Output	960lm	
Colour Temperature Lumen Output Light Efficiency	960lm 60lm/W	
Colour Temperature Lumen Output Light Efficiency CRI	960lm	
Colour Temperature Lumen Output Light Efficiency	960lm 60lm/W	
Colour Temperature Lumen Output Light Efficiency CRI	960lm 60lm/W	
Colour Temperature Lumen Output Light Efficiency CRI	960lm 60lm/W	
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	960lm 60lm/W	
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	960lm 60lm/W 80	
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length	960lm 60lm/W 80 27cm	
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width	960lm 60lm/W 80 27cm 27cm	
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height	960lm 60lm/W 80 27cm 27cm 8cm	
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight	960lm 60lm/W 80 27cm 27cm 8cm 0,9Kg	

Energy Label



Certification & Warranty	
Warranty	2 Years
Weee Directive	Yes