

15 Plafo>The LED Plafo Outdoor Square Plastic

67282BN/AN/W



30W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.





Downloads










Dimensions




Physical Specification

Item Group	15 Plafo
Family	The LED Plafo Outdoor Square Plastic
Order Code	67282BN/AN/W
Colour	Anthracite
Material	Plastic
Diffuser Material	PC
Shape	Rectangular
Length	400mm
Width	400mm
Height	83mm
Surface Ceiling	Yes
Indoor	Yes

Outdoor	Yes
Adjustable	No
IK Rating	8
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	38V
Power(Watts)	28W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	144
F Mark	F
Gear	

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	18,2-30W
Power Factor	0,9
Constant Current	Yes
700mA	26-43,5V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise
Illumination Data	
murimation Data	
	3000K
Colour Temperature	3000K
Colour Temperature Lumen Output	1800lm
Colour Temperature Lumen Output Light Efficiency	1800lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI	1800lm
Colour Temperature Lumen Output Light Efficiency	1800lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI	1800lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI	1800lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	1800lm 60lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	1800lm 60lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length	1800lm 60lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width	1800lm 60lm/W 80 110 110 110 110 110 110 110
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height	1800lm 60lm/W 80 41cm 41cm 10,5cm
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight	1800lm 60lm/W 80 41cm 41cm 10,5cm
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight Pcs/Carton	1800lm 60lm/W 80 41cm 41cm 10,5cm 2,6Kg

Energy Label



Certification	& W	/arrantv

Warranty	2 Years
Weee Directive	Yes