

15 Plafo>The LED Plafo Outdoor Square Plastic

67282BN/G/W



30W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions




Physical Specification

Item Group	15 Plafo
Family	The LED Plafo Outdoor Square Plastic
Order Code	67282BN/G/W
Colour	Grey
Material	Plastic
Diffuser Material	PC
Shape	Rectangular
Length	400mm
Width	400mm
Height	83mm
Surface Ceiling	Yes
Indoor	Yes

Outdoor	Yes
Adjustable	No
IK Rating	8
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	38V
Power(Watts)	28W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	144
F Mark	F
Gear	

Input Voltage 220-240V 50 Hz Yes 60 Hz Yes Power (Watts) 18,2-30W Power Factor 0.9 Constant Currient Yes 700mA 26-43,5V IP Rating IP20 Safety Class □ Dirmatele No Housing Material Plassic Output Terminal Connector Brand Eaglerise Illumination Data 2000K Lumen Output 1800fm Light Efficiency 00m/W CRI 00 Illumination Diagram 41cm Box Weight 41cm Box Weight 2,8Kg PssCarton 4 Barcode 5291889043454 HS Code 940510490	Gear Type	Led Driver
Power(Watts) 18,2 30W 18,2	Input Voltage	220-240V
Power (Watts) 18,2-30W	50 Hz	Yes
Power Factor 0.8 Constant Current Yes 700mA 26-43,5V IP Rating IP20 Safety Class □ Dimmable No Housing Material Plastic Output Terminal Connector Brand Eaglerise Illumination Data South Colour Temperature 3000K Lumen Output 1800/m Light Efficiency 60lm/W CRI 80 Illumination Diagram A1cm Box Length 41cm Box Weight 41cm Box Weight 2.6Kg Pes/Carton 4 Barcode 6291889043454	60 Hz	Yes
Constant Current Yes 700mA 26-43,5∨ IP Rating IP20 Safety Class □ Dimmable No Housing Material Plastic Output Terminal Connector Brand Eaglerise Illumination Data 4800/m Colour Temperature 3000/k Lumen Output 1800/m Light Efficiency 60/m/W CRI 80 Illumination Diagram 41cm Box Length 41cm Box Weight 41cm Box Weight 2,6Kg Pcs/Catron 4 Barcode 5291889043454	Power(Watts)	18,2-30W
TROMPA	Power Factor	0,9
PRating	Constant Current	Yes
Safety Class □ Dimmable No Housing Material Plastic Output Terminal Connector Brand Eaglerise Illumination Data Colour Temperature 3000K Lumen Output 1800lm Light Efficiency 60lm/W CRI 80 Illumination Diagram A Packing Info 41cm Box Length 41cm Box Width 41cm Box Height 10,5cm Box Weight 2,6kg Pcs/Carton 4 Barcode 5291889043454	700mA	26-43,5V
No Housing Material Plastic	IP Rating	IP20
Housing Material	Safety Class	
Output Terminal Connector Brand Eaglerise Illumination Data Colour Temperature 3000K Lumen Output 1800lm Light Efficiency 60lm/W CRI 80 Illumination Diagram ■ Packing Info 41cm Box Length 41cm Box Weight 10,5cm Box Weight 2,6Kg Pes/Carton 4 Barcode 5291889043454	Dimmable	No
Brand	Housing Material	Plastic
Colour Temperature	Output Terminal	Connector
Colour Temperature 3000K Lumen Output 1800lm Light Efficiency 60lm/W CRI 80 Illumination Diagram Illumination Diagram Packing Info ### After	Brand	Eaglerise
Colour Temperature 3000K Lumen Output 1800lm Light Efficiency 60lm/W CRI 80 Illumination Diagram Illumination Diagram Packing Info ### After		
Lumen Output 1800 lm Light Efficiency 60 lm/W CRI 80 Illumination Diagram Illumination Diagram Packing Info Box Length 41 cm Box Width 41 cm Box Height 10,5 cm Box Weight 2,6 Kg Pcs/Carton 4 Barcode 5291889043454	Illumination Data	
Lumen Output 1800 lm Light Efficiency 60 lm/W CRI 80 Illumination Diagram Illumination Diagram Packing Info 41 cm Box Weight 41 cm Box Weight 10,5 cm Box Weight 2,6 Kg Pcs/Carton 4 Barcode 5291889043454		
Light Efficiency 60 lm/W CRI 80 Illumination Diagram ✓ Packing Info 41 cm Box Length 41 cm Box Width 41 cm Box Height 10,5 cm Box Weight 2,6 kg Pcs/Carton 4 Barcode 5291889043454		200014
CRI 80 Illumination Diagram Illumination Diagram Packing Info Box Length Box Width 41cm Box Height 10,5cm Box Weight 2,6Kg Pos/Carton 4 Barcode 5291889043454	Colour Temperature	
Packing Info Box Length 41cm Box Width 41cm Box Height 10,5cm Box Weight 2,6Kg Pcs/Carton 4 Barcode 5291889043454	Colour Temperature Lumen Output	1800lm
Box Length 41cm Box Width 41cm Box Height 10,5cm Box Weight 2,6Kg Pcs/Carton 4 Barcode 5291889043454	Colour Temperature Lumen Output Light Efficiency	1800lm 60lm/W
Box Length 41cm Box Width 41cm Box Height 10,5cm Box Weight 2,6Kg Pcs/Carton 4 Barcode 5291889043454	Colour Temperature Lumen Output Light Efficiency CRI	1800lm 60lm/W
Box Length 41cm Box Width 41cm Box Height 10,5cm Box Weight 2,6Kg Pcs/Carton 4 Barcode 5291889043454	Colour Temperature Lumen Output Light Efficiency CRI	1800lm 60lm/W
Box Width41cmBox Height10,5cmBox Weight2,6KgPcs/Carton4Barcode5291889043454	Colour Temperature Lumen Output Light Efficiency CRI	1800lm 60lm/W
Box Height10,5cmBox Weight2,6KgPcs/Carton4Barcode5291889043454	Colour Temperature Lumen Output Light Efficiency CRI	1800lm 60lm/W
Box Weight 2,6Kg Pcs/Carton 4 Barcode 5291889043454	Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	1800lm 60lm/W 80
Pcs/Carton 4 Barcode 5291889043454	Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length	1800lm 60lm/VV 80 41cm
Barcode 5291889043454	Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width	1800lm 60lm/W 80 41cm 41cm
	Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height	1800lm 60lm/W 80 41cm 41cm 10,5cm
HS Code 9405104090	Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight	1800lm 60lm/W 80 41cm 41cm 10,5cm
	Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight Pcs/Carton	1800lm 60lm/W 80 41cm 41cm 10,5cm 2,6Kg
	Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight Pcs/Carton Barcode	1800lm 60lm/W 80 41cm 41cm 10,5cm 2,6Kg 4

Energy Label



Certification	& W	/arrantv

Warranty	2 Years
Weee Directive	Yes