

15 Plafo>Outdoor Slim LED Plafo Die cast

67362A/AN/W



25W LED slim plafo, IP54, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Physical Specification


Item Group	15 Plafo
Family	Outdoor Slim LED Plafo Die cast
Order Code	67362A/AN/W
Colour	Anthracite
Material	Die Cast
Shape	Rectangular
Length	238mm
Width	238mm
Height	46mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	25W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	350mA
Voltage	55V
Power(Watts)	19,25W
IP Rating	IP54
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Osram
LED Number	264
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V

50 Hz	Yes
60 Hz	Yes
Power(Watts)	17-25W
Power Factor	0,9
Constant Current	Yes
350mA	48-72V DC
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Eaglerise
Illumination Data	
Colour Temperature	3000K
Lumen Output	1600lm
Light Efficiency	75lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	
Packing Info	
Box Length	25,5cm
Box Width	25,5cm
Box Height	6,5cm
Box Weight	1,05kg
Pcs/Carton	8
Barcode	5291889039419
HS Code	9405409900

Energy Label



Certification & Warranty	
Warranty	2 Years
Weee Directive	Yes