



12W LED slim plafo, IP54, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	15 Plafo
Family	The LED Slim Plafo Range Round
Order Code	67366/W/C
Colour	White
Material	PC
Shape	Circular
Height	50mm
Diameter	250mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No

IK Rating

8

Electrical Characteristics

Gear

Built In

Fitting + Driver

Input Voltage

100-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

12W

IP Rating

IP54

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

160mA

Voltage

70V

Power(Watts)

11,2W

IP Rating

IP54

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Epistar

F Mark



Gear

Gear Type

Led Driver

Input Voltage

100-240V

50 Hz

Yes

60 Hz	Yes
Power(Watts)	12W
Power Factor	0,9
Constant Current	Yes
Output	160mA
Voltage Range	70V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable

Illumination Data

Colour Temperature	4000K
Lumen Output	960lm
Light Efficiency	80lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	

Packing Info

Box Length	26cm
Box Width	26cm
Box Height	5,7cm
Box Weight	0,8kg
Pcs/Carton	20
Carton Length	60cm
Carton Width	54cm
Carton Height	29cm
Carton Weight	16,1Kg


Barcode

5291889043041

HS Code

9405104090

Energy Label



Certification & Warranty

Warranty

2 Years

Weee Directive

Yes