

## 15 Plafo>The LED Slim Plafo Range PC

# 67370/W/C



25W LED slim plafo, IP54, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.





















#### Dimensions





#### **Physical Specification**


| Item Group      | 15 Plafo                    |
|-----------------|-----------------------------|
| Family          | The LED Slim Plafo Range PC |
| Order Code      | 67370/W/C                   |
| Colour          | White                       |
| Material        | PC                          |
| Shape           | Circular                    |
| Height          | 40mm                        |
| Diameter        | 350mm                       |
| Surface Ceiling | Yes                         |
| Indoor          | Yes                         |
| Outdoor         | Yes                         |
| Adjustable      | No                          |

### Electrical Characteristics

| Gear             | Built In         |
|------------------|------------------|
|                  |                  |
| Fitting + Driver |                  |
| Input Voltage    | 100-240V         |
| 50 Hz            | Yes              |
| 60 Hz            | Yes              |
| Safety Class     |                  |
| Power(Watts)     | 25W              |
| IP Rating        | IP54             |
| Light Source     | LED built in     |
| Dimmable         | No               |
| F Mark           | F                |
|                  |                  |
| Fitting          |                  |
| Input Type       | Constant Current |
| Input Current    | 300mA            |
| Voltage          | 80V              |
| Power(Watts)     | 24W              |
| IP Rating        | IP54             |
| Light Source     | LED built in     |
| LED Type         | SMD 2835         |
| LED Brand        | Epistar          |
| LED Number       | 335              |
| F Mark           | F                |
|                  |                  |
| Gear             |                  |
| Gear Type        | Led Driver       |
| Input Voltage    | 100-240V         |
|                  |                  |

| 50 Hz                | Yes           |
|----------------------|---------------|
| 60 Hz                | Yes           |
| Power(Watts)         | 18,6-24,8W    |
| Power Factor         | 0,9           |
| Constant Current     | Yes           |
| Output               | 310mA         |
| Voltage Range        | 60-80V        |
| IP Rating            | IP20          |
| Safety Class         |               |
| Dimmable             | No            |
| Housing Material     | Plastic       |
| Output Terminal      | Cable         |
|                      |               |
| lumination Data      |               |
|                      |               |
| Colour Temperature   | 4000K         |
| Lumen Output         | 2000lm        |
| Light Efficiency     | 80lm/W        |
| CRI                  | 80            |
| Illumination Diagram |               |
|                      |               |
| acking Info          |               |
|                      |               |
| Box Length           | 36cm          |
| Box Width            | 36cm          |
| Box Height           | 5cm           |
| Box Weight           | 1,4kg         |
| Pcs/Carton           | 10            |
| Barcode              | 5291889043102 |
| HS Code              | 9405104090    |
|                      |               |

Energy Label



Weee Directive

| Certification & Warranty |         |
|--------------------------|---------|
|                          |         |
| Warranty                 | 2 Years |

Yes