

19 Wall Recessed & Inground>The Inground Medium Series LED Aluminium

69016/W



3W COB LED inground, aluminium, for path illumination., IK08, IP67.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Gallery



Physical Specification

Item Group	19 Wall Recessed & Inground
Family	The Inground Medium Series LED Aluminium
Order Code	69016/W
Colour	Aluminium
Material	Aluminium
Shape	Circular
Height	105mm

Diameter	88mm
Cutout Hole Diameter	77mm
Inground	Yes
Depth Required	105mm+300mm drainage
Indoor	Yes
Outdoor	Yes
IK Rating	8
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	100-240V

50 Hz Yes 60 Hz Yes Safety Class Power(Watts) 3W IP67 IP Rating Light Source LED built in Dimmable No Cable Length 200cm F F Mark

Fitting	
Input Type	Constant Current
Input Current	350mA
Voltage	6V
Power(Watts)	2,8W
IP Rating	IP67
Light Source	LED built in
LED Type	SMD 1208


Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	1-4W
Power Factor	0,5
Constant Current	Yes
350mA	3-11V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	55°C
Housing Material	Plastic
Brand	Gallop
Ilumination Data	
Oeleva Terrar anatum	200014
Colour Temperature	3000K
Lumen Output	120lm
Light Efficiency	40lm/W
CRI	80
Illumination Diagram	
Packing Info	
Box Length	18,5cm
Box Width	12,5cm
Box Width Box Height	12,5cm 12,5cm
Box Width Box Height Box Weight	12,5cm 12,5cm 0,790Kg

Edison

LED Brand

Pcs/Carton	18
Barcode	5291889030171
HS Code	9405409900

Energy Label



Warranty Average Lifetime Weee Directive 2 Years 50000hours Yes