

19 Wall Recessed & Inground>The Dark Light Inground Range

69056A/W



3W COB LED inground, IP67.


Requires 24V driver.

Complies with standard EN60598-1 and any other specific standards.





Dimensions



Must be ordered separately



89015V

Physical Specification

Item Group

19 Wall Recessed & Inground

The Dark Light Inground Range
69056A/W
Aluminium
Natural Aluminium
Glass

Shape	Circular
Height	55mm
Diameter	55mm
Cutout Hole Diameter	50mm
Inground	Yes
Depth Required	100mm + 300mm drainage
Indoor	Yes
Outdoor	Yes
IK Rating	8

Electrical Characteristics

Fitting	
Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	
Power(Watts)	3W
IP Rating	IP67
Light Source	LED built in
LED Type	СОВ
LED Brand	Prolight
Cable Length	200cm
F Mark	F


Colour Temperature	3000K
Lumen Output	240lm
Light Efficiency	80lm/W
CRI	80
Beam Angle	38°

Dark Light

Yes

Packing InfoPcs/Carton50Barcode5291889064275HS Code9405409900

Energy Label



Certification & Warranty	
Warranty	3 Years
Weee Directive	Yes